

High Frequency Transistor


NPN Silicon

MPS5179


ON Semiconductor Preferred Device

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V_{CEO}	12	Vdc
Collector–Base Voltage	V_{CBO}	20	Vdc
Emitter–Base Voltage	V_{EBO}	2.5	Vdc
Collector Current — Continuous	I_C	50	mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	200 1.14	mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	300 1.71	mW mW/ $^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to +150	$^\circ\text{C}$



CASE 29-11, STYLE 1
TO-92 (TO-226AA)



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector–Emitter Sustaining Voltage ($I_C = 3.0$ mAdc, $I_B = 0$)	$V_{CEO(sus)}$	12	—	Vdc
Collector–Base Breakdown Voltage ($I_C = 0.001$ mAdc, $I_E = 0$)	$V_{(BR)CBO}$	20	—	Vdc
Emitter–Base Breakdown Voltage ($I_E = 0.01$ mAdc, $I_C = 0$)	$V_{(BR)EBO}$	2.5	—	Vdc
Collector Cutoff Current ($V_{CB} = 15$ Vdc, $I_E = 0$) ($V_{CB} = 15$ Vdc, $I_E = 0$, $T_A = 150^\circ\text{C}$)	I_{CBO}	— —	0.02 1.0	μAdc

ON CHARACTERISTICS

DC Current Gain ($I_C = 3.0$ mAdc, $V_{CE} = 1.0$ Vdc)	h_{FE}	25	250	—
Collector–Emitter Saturation Voltage ($I_C = 10$ mAdc, $I_B = 1.0$ mAdc)	$V_{CE(sat)}$	—	0.4	Vdc
Base–Emitter Saturation Voltage ($I_C = 10$ mAdc, $I_B = 1.0$ mAdc)	$V_{BE(sat)}$	—	1.0	Vdc

Preferred devices are ON Semiconductor recommended choices for future use and best overall value.

MPS5179

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Max	Unit
SMALL-SIGNAL CHARACTERISTICS				
Current-Gain — Bandwidth Product ⁽¹⁾ ($I_C = 5.0 \text{ mA dc}$, $V_{CE} = 6.0 \text{ V dc}$, $f = 100 \text{ MHz}$)	f_T	900	2000	MHz
Collector-Base Capacitance ($V_{CB} = 10 \text{ V dc}$, $I_E = 0$, $f = 0.1$ to 1.0 MHz)	C_{cb}	—	1.0	pF
Small Signal Current Gain ($I_C = 2.0 \text{ mA dc}$, $V_{CE} = 6.0 \text{ V dc}$, $f = 1.0 \text{ kHz}$)	h_{fe}	25	300	—

1. f_T is defined as the frequency at which $|h_{fe}|$ extrapolates to unity.