

Fiber Optic Filter Attenuators, SC, Flanged

SC, Flanged, 10 dB

CORNING

Corning SC fiber optic filter attenuators incorporate absorption filters in the centers of the adapter housings. In use, the filters are interposed between the end faces of mating plugs. Attenuation values from 5 to 20 dB are available in 5 dB increments. Each dB value is numerically marked for easy identification.

Features and Benefits

Fully compatible with SC fiber optic connectors

No intermateability concerns

Numerical identification mark on housing

Easy indication of attenuation levels

Attenuator incorporated inside standard SC adapter housings

Compatible with standard distribution panels

Specifications

General Specifications

Attenuator Type	Filter
Compatibility	SC
Packaging	Single Pack
Product Type	Attenuators

Temperature Range

Operation	-20 °C to 70 °C (-4 °F to 158 °F)
-----------	-----------------------------------

Design - Connector

Housing Material	Metal
------------------	-------

Mechanical Specifications - Connector

Durability	> 1000 matings without significant variation
Weight	0.4 g

Fiber Optic Filter Attenuators, SC, Flanged

SC, Flanged, 10 dB

CORNING

Optical Specifications - Connector

Attenuation at 1300 nm Operating Wavelength	10 dB
Attenuation at 1550 nm Operating Wavelength	7.6 dB
Attenuation at 820 nm Operating Wavelength	16 dB
Attenuation at 632 nm Operating Wavelength	23 dB
Attenuation Tolerance at 1300 nm	+/- 1.5 dB
Attenuation Tolerance at 1550 nm	+/- 1.5 dB
Reflectance	-15 dB
Reflectance, Typical	-17 dB

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	4059730
Product Description	SC Fiber Optic Filter Attenuators, Flanged
EAN Code	4056418197050

Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, SC



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING