



61292-1

**PICABOND® Connector, 1000 loose piece, 48 Vdc, yellow**

- Lightweight, compact, and economical means of splicing multiconductor telephone cable
- No prestripping or cutting required, can tap without service interruptions, eliminates “turndowns”
- Color-coded to indicate size and type of wire; used for butt, straight, bridge and half-tap splicing applications

## **OBSOLETE**

This product was discontinued on: June 1, 2016

### Replaced By

61292-2

PICABOND® Connector, 1000 loose piece, 400 Vdc, yellow

## Product Classification

Brand	PICABOND®
Product Series	PICABOND
Product Type	Splice
Regional Availability	Australia/New Zealand   EMEA   Latin America   North America

## Body Features

Cable Insulation Material	Air Core PIC   Foam Filled PIC
Color Code	Yellow
Sealant	Gel filled

## Contact Features

Contact Base Material	Brass
Contact Plating Material	Tin

## Dimensions

Wire Size (CMA)	24 – 19 AWG
-----------------	-------------

## Electrical Characteristics

Voltage Rating	48 Vdc
----------------	--------

## Packaging Features

Packaging Method	Loose Piece
Packaging Quantity	1000

## Product Type Features

Splicing Applications	Bridge   Butt   Full Bridge   Half-tap   Straight (In-line)
-----------------------	---

---

61292-1

## **Usage Conditions**

---

Operating Temperature -40 – 60 °C