



Images

11904C Test Port Adapter, 2.4 mm (m) to 2.92 mm (f), DC to 40 GHz

Sold By: **Keysight** - Usually arrives in 7 weeks
Authorized Sales Partners - [Check availability](#)

📄 [View Brochure](#) ▾

🛡️ [Visit Technical Support](#)

Base Price **Rs 70,296**

Typical Configuration ⓘ

Typical Configuration

11904C 2.4 mm male to 2.92 mm female adapter

[Get Quote](#)

[How to Buy or Rent](#)

👁️ [Add to My Watchlist](#)

Prices for: India

* Prices are subject to change without notice. Prices shown are Manufacturer's Suggested Retail Prices (MSRP).

Overview & Features

Document Library

Key Features & Specifications

Superior RF Performance

- Return Loss: > 24 dB
- Repeatability: -40 dB

Features

- Electrical Length: 11.3 mm (0.45 in)
- Overall Length: 13.3 mm (0.52 in)

- Diameter: 9.0 mm (0.35 in)

Description

The 11904C is a metrology grade, 2.4 mm male to 2.92 mm female adapter with dc to 40 GHz operation. It is 13.3 mm in length and has a diameter of 9 mm.

Learn more about [Keysight adapters, 2.4 mm, 2.92 mm](#)

Product Support Center

- [Technical Support](#)
manuals, drivers, application notes, firmware, software, ...
- [Parts](#)
- [Repair & Calibration Services](#)

Training & Events

- [All Webcast On-Demand Recordings](#)
- [H7215A/B-101 RF & Microwave Measurement Fundamentals](#)
- [H7215A/B-166 Transmission Line Fundamentals](#)

▶ [View All](#)

myKeysight

- [My Products](#)
- [My Watchlist](#)
- [My Download History](#)
- [My News](#)

Buy

- [How to Buy or Rent](#)
- [Request a Quote](#)
- [Find a Partner](#)
- [See Special Offers](#)
- [Check Order Status](#)
- [View Trade-In Offers](#)
- [Browse Used Equipment](#)
- [Why Buy Keysight](#)

Support Tasks

- [Manage Software Licenses](#)
- [Find a Manual](#)
- [Update Firmware/Software](#)
- [Browse Application Notes](#)
- [Request Repair or Calibration](#)
- [Check Warranty Status](#)
- [Ask the Community](#)
- [Find a Part](#)

Legal

- [Privacy](#)
- [Terms](#)
- [Trademark Acknowledgements](#)