

C2937


REV
A

COEV MAGNETICS

tyco Electronics

Product Description

**CEP7 Line Isolation Transformer
EN60950 / 250V**



Information subject to change without notice. 12/02

Primary units are in inches. Millimeters are in brackets.

Electrical Specifications at +20°C unless noted otherwise

Test Description	Limit	Units	Tol	Notes
Inductance	100	μH	±5%	1-4 tie(2+3), 10kHz, 100mVAC, 0ADC, Ls.
Inductance	100	μH	±6%	1-4 tie(2+3), 10kHz, 100mVAC, 120ADC, Ls.
Leakage Inductance	8.5	μH	Max.	1-4 tie(2+3, 6+7, 8+5), 100kHz, 100mVAC, Ls.
DC Resistance	0.440	Ω	Max.	1-3
DC Resistance	0.440	Ω	Max.	2-4
DC Resistance	0.495	Ω	Max.	7-6
DC Resistance	0.495	Ω	Max.	8-5
Turns Ratio	1.39 : 1.00	---	±2%	(1-4) : (7-5) tie(2+3, 6+8), 10KHz, 100mVAC.
Dielectric	1,875	VAC	500μA	1-7 tie(2+3, 6+8), 1 second test, 500μA maximum leakage current.
Dielectric	500	VAC	500μA	1-2, 1 second test, 500μA maximum leakage current.
Total Harmonic Distortion	-78	dB	Max.	30 KHz, 3.15Vrms, Line : IC
Longitudinal Balance	46	dB	Min	@ 1.1 MHz

Temperature Range: -40°C to +85°C.

Patent Pending

The information contained in this drawing is the sole property of CoEv, Inc. Any reproduction or use without the written permission of CoEv, Inc. is prohibited.

TEL 888-978-2638 - FAX 605-886-8995 - Specifications subject to change without notice. For latest revision visit www.tycopowercomponents.com