

Build-Out Optical Attenuators, ST[®] Compatible

ST[®] Compatible, 14 dB

CORNING

Corning universal build-out optical attenuators are used to interconnect single-mode connectors with or without attenuation. The ST[®] compatible attenuator styles are available in 0-16, 18 and 20 dB levels. Each build-out attenuator requires the use of a build-out block (sold separately) that replaces the standard adapter. The ST compatible build-out block is equipped with a lock washer and circular nut for mounting into ST compatible bulkhead adapter panels. The unique design of these attenuators allows for easy change-out of attenuation values with no tools required and the 0 dB offering is very useful for connections where no additional attenuation is required.

Features and Benefits

Dual-wavelength design

Operable at 1310 and 1550 nm

Easy change-out of attenuation values

No tools required

Single-mode precision sleeve

Provides precise alignment



Part Number: ATN-37U-BO-14



Part Number: ATN-37U-BO-14

Build-Out Optical Attenuators, ST[®] Compatible

ST[®] Compatible, 14 dB

CORNING

Specifications

General Specifications	
Attenuator Type	Build-Out
Compatibility	ST [®] Compatible
Product Type	Attenuators
Packaging	Single Pack

Temperature Range	
Operation	-40 °C to 65 °C (-40 °F to 149 °F)

Design - Connector	
Housing Material	Composite

Optical Specifications - Connector	
Attenuation	14 dB
Attenuation Tolerance	± 2.1 dB
Reflectance	≤ -40 dB

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

Ordering Information

Part Number	ATN-37U-BO-14
Product Description	ST [®] Compatible Build-Out Optical Attenuator

Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, ST [®] Compatible

Build-Out Optical Attenuators, ST[®] Compatible

ST[®] Compatible, 14 dB



CORNING

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2014 Corning Optical Communications. All rights reserved.