



Fork Terminals



These fork terminals have extra-long PVC insulation sleeve for protection and stress relief at wire's flex point. Brazed seam barrel is serrated for high pull-out value. Terminal is high conductivity electrolytic copper, electro-tin plated. Insulation is color-coded.

Stock thickness same as ring terminal of same size.



Vinyl Insulated Fork—Insulation Support



Cat. No.	Bulk Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lbs. Per 1000	Dimensions			
							A	B	C	M
18RA-6F	RA1167	100/1M	22-16	.150	#6	5	.94	.25	.27	.81
18RA-8F	RA1147	100/1M	22-16	.150	#8	5	.97	.31	.27	.81
18RA-10F	RA1157	100/1M	22-16	.150	#10	5	.97	.31	.27	.81
14RB-6F	RB647	100/1M	18-14	.170	#6	6	.97	.31	.27	.81
14RB-6FS†	—	100	18-14	.170	#6	6	.89	.30	.25	.75
14RB-8F	RB657	100/1M	18-14	.170	#8	6	.97	.31	.27	.81
14RB-10F	RB1157	100/1M	18-14	.170	#10	6	.97	.31	.27	.81
14RB-14F	RB1717	100/1M	18-14	.170	¼"	6	1.11	.44	.38	.89
10RC-6F	RC1337	50/500	12-10	.210	#6	7	1.09	.38	.27	.90
10RC-8F	RC1147	50/500	12-10	.210	#8	7	1.09	.38	.27	.90
10RC-10F	RC1157	50/500	12-10	.210	#10	7	1.09	.38	.27	.90
10RC-14F	RC1167	50/500	12-10	.210	¼"	7	1.15	.50	.37	.90

U.L. Listed E-9809

Installing tools: WT145C, WT2000, WT112M, ERG-2001, ERG-2003, WT1455, WT2130A (RC)

† Turned-up toes

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

For Mil Specs listing, please refer to page C73.