

RCC2-11-08-F



RCC2-11-08-M



RCC2-23-63-M-SR



RCC2-23-63-F



*Note: Wire supplied by others. Not assembled by Samtec. Pin or Socket must be specified separately.

RUGGED CIRCULAR RCC2 SERIES

SPECIFICATIONS

For complete specifications see www.samtec.com?RCC2

Insulator Material:
Black Thermoplastic
Pin Material:
See T-1R31
Socket Material:
See C-198
Operating Temp Range:
-55°C to +125°C

Requires:
Pin T-1R31 or
Socket C-198 and
customer assembly

Optional Strain Relief
(Cable Clamp)

Ideal for
high shock,
high vibration
applications

Shell sizes
11, 17 and 23

High
Density

Polarized
and keyed

ALSO AVAILABLE

Assembly Tooling.
Contact atg@samtec.com

Locking collar,
Align & Latch™
features

8, 9, 28, 57
or 63 positions

RCC2	SHELL SIZE	NO. OF POSITIONS	GENDER	OPTION												
SPECIFY FROM CHART																
			-F = Female -M = Male	-SR = Strain Relief (Cable Clamp)												
<table border="1"> <thead> <tr> <th>SHELL SIZE</th> <th>A (DIA)</th> <th>B (SQ)</th> </tr> </thead> <tbody> <tr> <td>-11</td> <td>(23,93) .942</td> <td>(28,58) 1.125</td> </tr> <tr> <td>-17</td> <td>(33,40) 1.315</td> <td>(36,45) 1.435</td> </tr> <tr> <td>-23</td> <td>(44,43) 1.743</td> <td>(44,45) 1.750</td> </tr> </tbody> </table>					SHELL SIZE	A (DIA)	B (SQ)	-11	(23,93) .942	(28,58) 1.125	-17	(33,40) 1.315	(36,45) 1.435	-23	(44,43) 1.743	(44,45) 1.750
SHELL SIZE	A (DIA)	B (SQ)														
-11	(23,93) .942	(28,58) 1.125														
-17	(33,40) 1.315	(36,45) 1.435														
-23	(44,43) 1.743	(44,45) 1.750														

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM