


## CB-1026D-30 Product Details



### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

**Product Highlights:**


- CB Series
- Input Voltage = 24 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 30 VDC or 277 VAC
- Mounting Options = Socket


[View all Features](#)


### Quick Links


- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)


**CB-1026D-30**  
(1-1393136-8)  
TE Internal Number: 1-1393136-8

 [Active](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"><li>• <a href="#">CB CMOS IC Time Delay Relay</a> (PDF, English)</li></ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Product Line Information</a></li></ul> <p><b>Additional Product Images:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Schematic</a></li><li>• <a href="#">Wiring Diagram</a></li></ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Tooling</a></li></ul>
<a href="#">List all Documents</a>	

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"><li>• Termination Type = 8-Pin Octal Style Plug</li></ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"><li>• Input Voltage (VDC) = 24</li><li>• Contact Rating = 10A @ 30 VDC or 277 VAC</li></ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Series</a> = CB</li></ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"><li>• Mounting Options = Socket</li><li>• Mode of Operation = Delay on Operate</li><li>• Delay Time = 0.1 seconds to 1 second</li><li>• Type of Control = Knob</li><li>• Repeatability, Max. = ± 2%</li><li>• Approved Standards = CSA Certified, UL Recognized</li><li>• Contact Base Material = Silver Cadmium Oxide</li><li>• Approx. Dimensions (L x W x H) (mm [in]) = 61.10 x 45.20 x 74.60 [2.407 x 1.780 x 2.939]</li><li>• Enclosure = White Plastic Case</li></ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Contact Arrangement</a> = 2 Form C, DPDT, 2 C/O</li><li>• Multiple Timing Ranges = Without</li></ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"><li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li><li>• <a href="#">Lead Free Solder Processes</a> = Not relevant for lead free process</li></ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"><li>• Temperature Range (?C) = -10 – +55</li></ul> <p><b>Other:</b></p> <ul style="list-style-type: none"><li>• Brand = Potter &amp; Brumfield</li></ul>

### Corporate Information

[Who We Are](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)

### Quick Links

[Check Distributor Inventory](#)  
[Cross Reference](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

### Customer Support

[Email or Chat with Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage Your Account](#)