

# Product data sheet

Specifications



Circuit breaker, PowerPacT B,  
45A, 1 pole, 600Y/347VAC, 18kA,  
lugs, thermal magnetic, 80%

BGL16045

## Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | PowerPact       |
| Product Name              | PowerPact B     |
| Device Short Name         | BG 045          |
| Product Or Component Type | Circuit breaker |
| Device Application        | Distribution    |

## Complementary

|  |  |
|--|--|
| Line Rated Current                     | 45 A   |
| Number Of Poles                        | 1P   |
| Protected Poles Description            | 1t   |
| Control Type                           | Toggle   |
| Breaking Capacity Code                 | G  |
| Breaking Capacity                      | 65 kA 208Y/120 V AC 50/60 Hz UL 489<br>65 kA 240 V AC 50/60 Hz UL 489<br>35 kA 480Y/277 V AC 50/60 Hz UL 489<br>20 kA 600Y/347 V AC 50/60 Hz UL 489<br>20 kA 125 V DC UL 489 |
| [Ue] Rated Operational Voltage         | 240 V AC 50/60 Hz UL 489   |
| Network Frequency                      | 50/60 Hz   |
| [Ics] Rated Service Breaking Capacity  | 65 kA 220...240 V AC 50/60 Hz IEC 60947-2  |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV IEC 60947-2   |
| Trip Unit Technology                   | Thermal-magneticTM-D,  |
| Continuous Current Rating              | 80 %   |
| [Ui] Rated Insulation Voltage          | 800 V IEC 60947-2  |
| Trip Unit Name                         | TM-D   |
| Suitability For Isolation              | Yes IEC 60947-2  |
| Utilisation Category                   | Category A   |
| Mechanical Durability                  | 15000 cycles IEC 947-1 Annex F ed 5.2  |
| Electrical Durability                  | 10000 cycles IEC 947-1 Annex K ed 5.2 In   |
| Connection Pitch                       | 1.06 in (27 mm)  |
| Awg Gauge                              | AWG 6...AWG 2/0 fine stranded aluminium/copper<br>AWG 14...AWG 3/0 rigid or stranded aluminium/copper  |
| Mounting Mode                          | Clip-on 35 mm symmetrical DIN rail)<br>By screws plate)  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                    |  |
|------------------------------------|--|
| <b>Electrical Connection</b>       | Everlink lug, line<br>Everlink lug, load   |
| <b>Tightening Torque</b>           | 44.25 lbf.in (5 N.m) 0.00...0.02 in <sup>2</sup> (2.5...16 mm <sup>2</sup> ) (AWG 14...AWG 4)<br>79.66 lbf.in (9 N.m) 0.04...0.15 in <sup>2</sup> (25...95 mm <sup>2</sup> ) (AWG 3...AWG 3/0) |
| <b>Power Wire Stripping Length</b> | 0.79 in (20 mm)  |
| <b>Color</b>                       | Gray RAL 7016)   |
| <b>9 Mm Pitches</b>                | 3  |
| <b>Height</b>                      | 5.39 in (137 mm)   |
| <b>Width</b>                       | 1.06 in (27 mm)  |
| <b>Depth</b>                       | 3.15 in (80 mm)  |
| <b>Net Weight</b>                  | 1.12 lb(US) (0.51 kg)  |
| <b>Quantity Per Set</b>            | Set of 1   |
| <b>Circuit Breaker Application</b> | HACR rated   |

## Environment

|  |   |
|--|---|
| <b>Quality Labels</b>                        | CE  |
| <b>Standards</b>                             | EN/IEC 60947-5-1<br>NEMA AB1<br>CSA C22.2 No 5<br>UL 489<br>EN/IEC 60947-2<br>GB 14048.2<br>NMX J-266 |
| <b>Product Certifications</b>                | UL<br>IEC<br>CCC<br>EAC<br>CSA<br>NOM   |
| <b>Ip Degree Of Protection</b>               | Front cover IP40 IEC 60529  |
| <b>Ik Degree Of Protection</b>               | IK07 IEC 62262  |
| <b>Pollution Degree</b>                      | 3 IEC 60947-1   |
| <b>Ambient Air Temperature For Operation</b> | -13...158 °F (-25...70 °C)  |
| <b>Ambient Air Temperature For Storage</b>   | -58...185 °F (-50...85 °C)  |
| <b>Operating Altitude</b>                    | 6561.68 ft (2000 m) without derating<br>5000 m with derating  |

## Ordering and shipping details

|                          |                                    |
|--------------------------|------------------------------------|
| <b>Category</b>          | 01131-BG UNIT MOUNT BREAKER/SWITCH |
| <b>Discount Schedule</b> | DE2                                |
| <b>Gtin</b>              | 03606481193346                     |
| <b>Returnability</b>     | No                                 |

## Packing Units

|                                     |                  |
|-------------------------------------|------------------|
| <b>Unit Type Of Package 1</b>       | PCE              |
| <b>Number Of Units In Package 1</b> | 1                |
| <b>Package 1 Height</b>             | 1.42 in (3.6 cm) |
| <b>Package 1 Width</b>              | 4.72 in (12 cm)  |

---

**Package 1 Length** 7.48 in (19 cm)

---

**Package 1 Weight** 16.01 oz (454 g)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

 Pvc Free

 Halogen Free Product

## Certifications & Standards

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information.

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

**California Proposition 65**

WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)