



1. Crimped ferrule: Hex crimp size .213" (5.41mm)
2. Crimped contact pin: Hex crimp size .068" (1.72mm)

Name	Material	Finish
Body	Brass per QQ-B-626	Nickel 70μ" over copper strike
Insulator	Delrin	White
Washer	SS41	Nickel 70μ" over copper strike
Spring	SK5	Nickel 70μ" over copper strike
C ring	SS41	Nickel 70μ" over copper strike
Gasket	Rubber	Red
Shell	Brass per QQ-B-626	Nickel 70μ" over copper strike
Contact pin	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper strike
Ferrule	Brass JIS H 3250, C 2700	Nickel 70μ" over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/03/07
				Checked	Lizzy	03/03/07
				Drawn	Tina	03/03/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7011NS-502CFB-A**

Description: BNC crimp plug, for RG-55/U, 142A/U, 223/U, 400/U, 50 ohms