


SRMB2.5/12-FW1-12B

- 24 Connections
- Direct mounting
- With labelling on both sides





Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	2.5 mm ²	Stripped Length	7.0 mm
Clamping Range min	0.2mm ²	Width	5.0 mm
Clamping Range max	4.0 mm ²	Height	23.0 mm
		Length	75.4 mm
		Length Hole Direct Mounting	68.3 mm

Colours

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015

Connection Diagram



Order Data

Article Designation	Article Number	PU
SRMB2.5/12-FW1-12B-BEIGE	41358.2	20
SRMB2.5/12-FW1-12B-BLUE	41358.5	20

Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/5/11	492032.0	50
External Cross-Connector insulated AQ13/5/11	492033.0	50
External Cross-Connector insulated AQ14/5/11	492044.0	10
External Cross-Connector insulated AQ110/5/11	492045.0	10

Ratings

Ratings	UR		IEC
	Rated Voltage	300 V	300 V
Rated Current	20 A	20 A	24 A
Rated Wire Size	AWG 22-12	AWG 22-12	2.5 mm ²
Rated Impulse Voltage			6 V
Pollution Degree			3