







.250 Quick-Connect Series
In-Line Type

— Axial Bridge Design —
 To Accept .250 x .032 Male Tab

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	20-14	.075-.150	✓ ✓	4000	$\frac{7}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass	3000H 219A-5
							Brass	3000H 219AB-5
	20-14	None	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass	3000H 219A-5-2
							Brass	3000H 219AB-5-2
	20-14	.075-.175	✓ ✓	4000	$\frac{7}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 19A-5
							Brass	3000H 19AB-5
	20-14	None	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 19A-5-2
							Brass	3000H 19AB-5-2
	20-14	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 9A
							Brass	3000H 9AB
							Silver Plated Brass	3000H 9AC
	20-14	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 9A-2
							Brass	3000H 9AB-2
							Silver Plated Brass	3000H 9AC-2