

16MM MINIATURE PANEL SEALED METAL

The 57M is a miniature switch designed for rugged environments. The housing is zinc alloy with velour chrome plating. It is available as maintained or momentary action, solid-state operation with Gold plated contacts and solder terminals. It is ideal for a multitude of applications.


APPLICATIONS

- Security Equipment
- Industrial Control
- Medical Equipment
- Military Equipment
- Food Processing
- Transportation
- Computers

KEY FEATURES:

- Zinc Alloy/Velour Chrome Plated
- Center Spot LED and Non-Lighted Versions
- Maintained or Momentary Action
- Panel Sealed to IP67
- RoHS Compliant
- Solid State
- Gold Plated Contacts and Terminals

Series 57M-SS



ACTUAL SIZE

ORDERING INFORMATION:

SWITCH FUNCTION:

3. SOLID STATE, MOMENTARY, SOLDER TERMINAL
4. SOLID STATE, MAINTAINED, SOLDER TERMINAL
7. SOLID STATE, MOMENTARY, PC TERMINAL
8. SOLID STATE, MAINTAINED, PC TERMINAL
- C. SOLID STATE, , MOMENTARY, WIRE LEADS
- D. SOLID STATE, , MAINTAINED, WIRE LEADS
9. SPECIAL, DIGITS ARE IN SERIAL ORDER

HOUSING MATERIAL:

1. ZINC ALLOY, VELOUR CHROME PLATED
2. ZINC ALLOY, MIRROR BLACK

ILLUMINATION †:

0. NON-LIT
1. CENTER SPOT ILLUMINATION
2. RING ILLUMINATION
3. STANBY LOGO ILLUMINATION

LED COLOR:

- N. NONE
G. GREEN L.E.D.
R. RED L.E.D.
A. AMBER L.E.D.
B. BLUE L.E.D.
W. WHITE L.E.D.
RB. RED/BLUE L.E.D.
RG. RED/GREEN L.E.D.

VOLTAGE RESISTOR

- If BLANK *
05 5V FORWARD
12 12V FORWARD **
24 24V FORWARD **


57M- [] [] [] [] []

† Lighted switches come with wires on LEDs to protect from solder heat.
* Current limiting resistor is required to limit LED forward current to 20 mA (not included).
** 12 and 24 V resistors are available with wirelead versions only.

STANDARDS / AGENCY / RATINGS:



PRODUCT DRAWINGS



MECHANICAL CHARACTERISTICS

CIRCUIT:

SPST-NO-DB (FORM X)

BUTTON TRAVEL (NOM):

[2.3] .09

OPERATING FORCE (NOM):

[3N] 306g

PANEL THICKNESS:

[0.0 to 6.0] .00 to .24

NUT TORQUE (MAX):

[11.5 kgf/cm] 10 lb/in

HARDWARE:

BULK PACKAGED SEALING WASHER AND HEX NUT ARE INCLUDED.

ENVIRONMENTAL SPECIFICATIONS

ACTUATOR INGRESS PROTECTION:

IP67

OPERATING TEMPERATURE:

NON-LIT: [-40 C to +85 C]

-40 F to +185 F

ILLUMINATED: [-25 C to +85 C]

-13 F to +185 F

ELECTRICAL SPECIFICATIONS

SUPPLY VOLTAGE:

4.2V TO 24V, 26.5 MAX

SUPPLY CURRENT:

B < Brp, Vcc=12V:

3mA TYP to 8mA MAX

B > Bop, Vcc=12V:

4mA TYP to 8mA MAX

OUTPUT LOAD:

SINKING (I out MAX = 25mA)

REVERSE BATTERY VOLTAGE:

-30V MAX

REVERSE OUTPUT CURRENT:

-50mA MAX

SWITCH LIFE:

MOMENTARY: 1,000,000 CYCLES

MAINTAINED: 50,000 CYCLES

WIRE LEADS:

UL STYLE 1007

26 AWG, STRANDED