


Photodarlington Output: GaAs Input									
Part Number	CTR @ 10 mA I _F (%)		BV _{CEO} (V)	BV _{CBO} (V)	V _{CE (sat)} (V)	t _{ON} /t _{OFF} (μs)	V _{ISO AC} [RMS]	Pkg dwg	Agency Approvals (see pg 23)
	min	max	min	min	max	max			
4N29	100	—	30	30	1.0	5/40	5.3 kV	C	A, B, D, F, N, S, U
4N29.300	100	—	30	30	1.0	5/40	5.3 kV	C	A, B, D, F, N, S, U, V
4N30	100	—	30	30	1.0	5/40	5.3 kV	C	A, B, D, F, N, S, U
4N30.300	100	—	30	30	1.0	5/40	5.3 kV	C	A, B, D, F, N, S, U, V
4N31	50	—	30	30	1.2	5/40	5.3 kV	C	A, B, D, F, N, S, U
4N31.300	50	—	30	30	1.2	5/40	5.3 kV	C	A, B, D, F, N, S, U, V
4N32	500	—	30	30	1.0	5/100	5.3 kV	C	A, B, D, F, N, S, U
4N32.300	500	—	30	30	1.0	5/100	5.3 kV	C	A, B, D, F, N, S, U, V
4N33	500	—	30	30	1.0	5/100	5.3 kV	C	A, B, D, F, N, S, U
4N33.300	500	—	30	30	1.0	5/100	5.3 kV	C	A, B, D, F, N, S, U, V
CNX48U	600	—	30	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U
CNX48U.300	600	—	30	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U, V
H11B1	500	—	25	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U
H11B1.300	500	—	25	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U, V
H11B2	200	—	25	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U
H11B2.300	200	—	25	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U, V
H11B255	100	—	55	55	1.0	—	5.3 kV	C	A, B, D, F, N, S, U
H11B255.300	100	—	55	55	1.0	—	5.3 kV	C	A, B, D, F, N, S, U, V
H11B3	100	—	25	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U
H11B3.300	100	—	25	30	1.0	—	5.3 kV	C	A, B, D, F, N, S, U, V



Photodarlington Output: GaAs Input (No base connection) (4-Pin)									
Part Number	CTR @ 10 mA I _F (%)		BV _{CEO} (V)	BV _{CBO} (V)	V _{CE (sat)} (V)	t _{ON} /t _{OFF} (μs)	V _{ISO AC} [RMS]	Pkg dwg	Agency Approvals (see pg 23)
	min	max	min	min	max	max			
H24B1	1000	—	30	7	1.0	—	3.75 kV	F	U
H24B2	400	—	30	7	1.0	—	3.75 kV	F	U

