



RECOMMENDED MOUNTING HOLE

NOTE:
1. CAPTURED CENTER CONTACT.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
040	REDRAWN IN CAD, UPDATED FORMAT & MTG HOLE, ECN 90-0275-1	KCM 8/24/89	<i>PJA</i> 1/15/90

COMPONENT	MATERIAL	FINISH
HOUSING MOUNTING NUT	HALF HARD BRASS PER QQ-B-626, COMP 360	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
DIELECTRIC	TFE FLUOROCARBON PER MIL-P-19468 AND FED SPEC L-P-403 AND ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER QQ-C-530, ALLOY 173	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
LOCKWASHER	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		DRAWN BY RMK DATE 2/21/70		 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
FRAC.	DEC.	ANGLES	CHECKED BY 2/24/70		
± 1/64	±.005	± °	APPD BY D.NANIA DATE 2/28/70		
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		USE ASS'Y PROCEDURE		TITLE SMC SCREW-ON BULKHEAD JACK RECEPTACLE SOLDER POT TERMINAL	
NO. AP. N/A		SIZE B	CODE IDENT NO. 26805	5056-0000-09	REV 040
		SCALE 8:1			SHEET 1 OF 1