



UPC10XX


PHOTOCOUPLER

4 PIN PHOTOTRANSISTOR PHOTOCOUPLER

■ DESCRIPTION

The UTC **UPC10XX** is a 4 pin phototransistor photocoupler, it uses UTC's advanced technology to provide the customers with high isolation voltage between input and output, etc.

The UTC **UPC10XX** is suitable for programmable controllers and telecommunication equipments, etc.




■ FEATURES

Current transfer ratio (CTR : MIN. 50% at $I_f = 5mA, V_{CE} = 5V, T_A=25^{\circ}C$)

- * High input-output isolation voltage ($V_{ISO} = 5,000V_{rms}$)
- * High collector-emitter voltage ($V_{CEO} = 70V$)
- * Temperature range $-55^{\circ}C$ to $110^{\circ}C$
- * Creepage distance > 8mm
- * Employs double transfer mold technology

■ SYMBOL




■ ORDERING INFORMATION

| Ordering Number | | Package | Pin Assignment | | | | Packing |
|-----------------|-----------------|---------|----------------|---|---|---|-----------|
| Lead Free | Halogen Free | | 1 | 2 | 3 | 4 | |
| UPC10XXL-LS04-R | UPC10XXG-LS04-R | LSOP-4 | A | K | E | C | Tape Reel |

Note: Pin Assignment: A: Anode K: Cathode E: Emitter C: Collector

| | |
|--|--|
| <p>UPC10XXG-LS04-R</p> <ul style="list-style-type: none"> (1)Packing Type (2)Package Type (3)Green Package (4)Rank | <ul style="list-style-type: none"> (1) R: Tape Reel (2) LS04: LSOP-4 (3) G: Halogen Free and Lead Free, L: Lead Free (4) Refer to TRANSFER CHARACTERISTICS |
|--|--|

■ MARKING



■ ABSOLUTE MAXIMUM RATING (T_A=25°C, unless otherwise specified)

| PARAMETER | | SYMBOL | RATINGS | UNIT |
|----------------------------|-----------------------------------|------------------|------------|------------------|
| Input | Forward Current | I _F | 60 | mA |
| | Peak Forward Current (1μs, Pulse) | I _{FP} | 1.5 | A |
| | Reverse Voltage | V _R | 6 | V |
| | Power Dissipation | P _D | 100 | mW |
| | Derating Factor | | 1 | mW/°C |
| Output | Power Dissipation | P _C | 150 | mW |
| | Derating Factor | | 1.5 | mW/°C |
| | Collector Current | I _C | 50 | mA |
| | Collector-Emitter Voltage | V _{CEO} | 80 | V |
| | Emitter-Collector Voltage | V _{ECO} | 7 | V |
| Total Power Dissipation | | P _{TOT} | 250 | mW |
| Isolation Voltage (Note 2) | | V _{ISO} | 5000 | V _{rms} |
| Operating Temperature | | T _{OPR} | -55 ~ +110 | °C |
| Storage Temperature | | T _{STG} | -55 ~ +125 | °C |

- Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
 2. AC for 1 minute, R.H.= 40~60% R.H. In this test, pins 1, 2 are shorted together, and pins 3, 4 are shorted together.


■ ELECTRICAL CHARACTERISTICS (T_A=25°C, unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-------------------------------------|-------------------|--|-----|------|-----|------|
| INPUT | | | | | | |
| Forward Voltage | V _F | I _F =50mA | | 1.3 | 1.4 | V |
| | | I _F =100mA | | 1.35 | 1.6 | V |
| Reverse Current | I _R | V _R =4V | | | 10 | μA |
| Input Capacitance | C _{IN} | V=0, f=1kHz | | 50 | | pF |
| OUTPUT | | | | | | |
| Collector-Emitter Dark Current | I _{CEO} | V _{CE} =20V, I _F =0mA | | | 100 | nA |
| Collector-Emitter Breakdown Voltage | BV _{CEO} | I _C =1mA, I _F =0mA | 80 | | | V |
| Emitter-Collector Breakdown Voltage | BV _{ECO} | I _E =100μA, I _F =0mA | 7 | | | V |

■ TRANSFER CHARACTERISTICS (T_A=25°C, unless otherwise specified)







| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT | |
|---|----------------------|--|--------------------|-----|-----|------|---|
| Collector Current | I _C | I _F =5mA, V _{CE} =5V | 2.5 | | 30 | mA | |
| Current Transfer Ratio | CTR | I _F =5mA, V _{CE} =5V | UPC1000 | 50 | | 600 | % |
| | | | UPC1001 | 100 | | 160 | % |
| | | | UPC1004 | 100 | | 200 | % |
| | | | UPC1005 | 50 | | 150 | % |
| | | | UPC1006 | 100 | | 300 | % |
| | | | UPC1007 | 80 | | 160 | % |
| | | | UPC1008 | 130 | | 260 | % |
| | | | UPC1009 | 200 | | 400 | % |
| | | | UPC1010 | 150 | | 300 | % |
| | | | UPC1019 | 250 | | 500 | % |
| | | I _F =1mA, V _{CE} =5V | UPC1002 | 22 | | | % |
| | | | UPC1003 | 34 | | | % |
| | | | UPC1014 | 56 | | | % |
| | | | UPC1015 | 63 | | 125 | % |
| I _F =10mA, V _{CE} =5V | UPC1018 | 100 | | 200 | % | | |
| | UPC1002 | 63 | | 125 | % | | |
| | UPC1003 | 100 | | 200 | % | | |
| UPC1014 | 160 | | 320 | % | | | |
| Collector-Emitter Saturation Voltage | V _{CE(sat)} | I _F =10mA, I _C =1mA | | | 0.3 | V | |
| Isolation Resistance | R _{IO} | V _{IO} =500Vdc, 40~60% R.H. | 1×10 ¹² | | | Ω | |
| Floating Capacitance | C _{IO} | V _{IO} =0, f=1MHz | | 0.3 | | pF | |
| Cut-Off Frequency | f _c | V _{CE} =5V, I _C =2mA, R _L =100Ω, -3dB | | 80 | | kHz | |
| Turn-On Delay Time (Note 1) | t _{D(ON)} | V _{CE} =5V, I _C =2mA, R _L =100Ω | | 5 | | μs | |
| Turn-Off Delay Time | t _{D(OFF)} | | | 4.2 | | μs | |
| Rise Time | t _R | | | 3 | 18 | μs | |
| Fall Time | t _F | | | 4.7 | 18 | μs | |

■ TEST CIRCUITS AND WAVEFORMS



Switching Time Test Circuit & Waveforms

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.