

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

©

COPYRIGHT - By -

## REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	N4	REVISED PER ECO-13-019645	14DEC2013	KH	MZ
	P	REVISED PER ECO-18-000972	24JUL2018	RS	MZ

.010 MAX GATE  
DEPRESSION PERMISSIBLE  
THIS AREA

#4-40 THREADED INSERT, 4 PLC  
MATERIAL: BRASS  
-3 ONLY

Ø.125  
4 HOLES

1.125±.025

.844±.010  
TYP

PERIPHERAL SEAL  
BONDED IN PLACE.  
SEE TABLE

.844±.010  
TYP

1.125±.025

.844±.010  
TYP

.844±.010  
TYP

PANEL CUTOUT  
SCALE 1:1

.420±.015

.094±.010

5/8-24 UNEF-2A THREAD

.688±.010  
DIA

.630 MAX

.125 MAX  
PANEL THK

.809 MAX

Ø.125<sup>+.007</sup><sub>-.000</sub> 4 HOLES

Ø.840

4 OBSOLETE

-	YES	YES	205841-4
205841-1 & 205841-3	YES	NO	205841-3
205841-2	NO	NO	205841-2
205841-1	NO	NO	205841-1
PART NUMBER LOCATED ON FLANGE EDGE	THREADED INSERTS	PERIPHERAL SEAL	PART NUMBER

.124  
.000  
.062  
.062  
.124

.141

.000

.091

.033

.925 DIA

MATING FACE

.802±.010

FREE HANGING  
(-2 ONLY)

1 CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACES OF CONNECTOR.

2 WILL ACCEPT (8) SIZE 20 PIN CONTACTS.

3 AMP LOGO AND PART NUMBER LOCATED ON ANY FLANGE EDGE SEE CHART FOR PART NUMBER

4 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 4/5/91

A.STAUB BG

CHK 7-24-92

W.G.LENKER

APVD -

PRODUCT SPEC

108-10024

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

**STE**

TE Connectivity Ltd.

NAME

RECEPTACLE ASSEMBLY, STD SEX,  
SERIES 2, 11-8, CPC

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C-205841

SCALE 2:1

SHEET 1 of 1

REV P

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[205841-2](#)