







Part Number	Operating Voltage Range (V)RMS	Maximum Load Current @ 40°C A(RMS)	Trans. Overvolt V(Pk)	Turn-On Signal (DC)	Dielectric Strength Input/Output V(RMS)	Minimum Off-State dv/dt @ Rated V 25°C V/μs	Maximum Off State Leakage μA	Case Outline Number (1)	Series
SP1210	20-140	1.0	300	10mA				MR4	<b>SP</b>  1 Form A
SP2210	20-280	3.0	450	10mA	4000	600	10		
SP6210	20-280	3.0	600	10mA					
DP1210	20-140		300	10mA				<b>MR2</b>  1 Form A	
DP1610	20-140		300	3.5V					
DP2210	20-280	1.0	450	10mA	4000	600	10		
DP2610	20-280		450	3.5V					
DP6210	20-280		600	10mA					
DP6610	20-280		600	3.5V					
CS5005	20-280		500	5mA				<b>MR1</b> <b>CS</b>  1 Form A	
CS5010	20-280	0.3	500	10mA					
CS6005	20-280		600	5mA	4000	1200	10		
CS6010	20-280		600	10mA					

**Wiring Diagram**

			
<b>Series</b>	<b>SP</b>	<b>DP</b>	<b>CS</b>

(1) For case outline drawing see page 0-2