


CERAMIC SMD TYPE

18 kHz to 20 kHz (SCO-53)

- 18.000 kHz to 20.000 kHz in 0.1 kHz steps
- High stability with AT-cut crystal
- External dimensions : 5.0 × 3.2
- 1.8 to 3.3 operating supply voltage range
- CMOS Output
- Tri-state function available



■ PART NUMBERING GUIDE

SCO - 533 20 A D S R - 20.000K	
SUPPLY VOLTAGE(V_{DD}) 3 : 3.3 V, 2 : 2.5 V, 1 : 1.8 V	
FREQUENCY STABILITY 20: ±20 ppm, 25: ±25 ppm 50: ±50 ppm, BLANK : ±100 ppm	
OPERATING TEMPERATURE RANGE A: -40 to 85 °C, B: -20 to 70 °C C : 0 to 70 °C	
DUTY CYCLE D: 45/55, E : 40/60	
	FREQUENCY K : kHz
	PACKAGE OPTION R : TAPE AND REEL BLANK : BULK
	PIN 1 CONNECTION S : TRI-STATE, E/D BLANK : NO CONNECTION



■ ELECTRICAL SPECIFICATIONS

ITEM	Value	Remarks
Output Logic Type	CMOS	CMOS XO
Frequency *	18.000 kHz to 20.000 kHz	
Supply Voltage(V _{DD})	1.8 V _{DC} ±5 %, 2.5 V _{DC} ±5 %, 3.3 V _{DC} ±5%	
Operating Temperature Range	0 to +70 °C, -20 to +70 °C, -40 to +85 °C	
Storage Temperature Range	-55 to 125 °C	
Frequency Stability	±20 ppm, ±25 ppm, ±50 ppm, ±100 ppm Max.	Over operating temperature range
Input Current	5 mA Max.	
Output Voltage Logic High(V _{OH})	90 % of V _{DD} Min.	
Output Voltage Logic High(V _{OL})	10 % of V _{DD} Max.	
Rise / Fall Time	100 ns Max.	Measured at 10 % to 90 % of waveform
Duty Cycle	45 to 55 %	Measured at 50 % of waveform
Start-up Time	10 ms Max.	
Output Load Condition(CMOS)	15 pF Max.	
Output Enable Function (VIH and VIL)	70 % of V _{DD} min. to Enable Output 30 % of V _{DD} max. to Enable Output	High Impedance
Frequency Aging	±5 ppm Max.	25°C, First year

* Please contact us about developed standard frequencies



MECHANICAL DIMENSIONS (mm)

LAND PATTERN (mm)



TEST CIRCUIT (CMOS)

WAVEFORM (CMOS)




ENVIRONMENTAL & MECHANICAL SPECIFICATIONS

Temperature Cycling	MIL-STD-883, Method 1010, Condition B
Fine Leak Test	MIL-STD-883, Method 1014, Condition A
Gross Leak Test	MIL-STD-883, Method 1014, Condition C
Mechanical Shock	MIL-STD-883, Method 2002, Condition B
Vibration	MIL-STD-883, Method 2007, Condition A
Moisture Resistance	MIL-STD-883, Method 1004
Moisture Sensitivity	J-STD-020, MSL 1
Resistance to Soldering Heat	MIL-STD-202, Method 210, Condition K
Solderability	MIL-STD-883, Method 2003

REFLOW PROFILE

MARKING GUIDE



Frequency

LINE 1 : **XX.XXX K**

LINE 2 : **● S Y WW**

Sunny


Year

Week

kHz

TAPE AND REEL DIMENSIONS

MAT'L : P.S
COLOR : WHITE&BLACK
REFERANCE R=0.2



MAT'L : P.S
COLOR : WHITE&BLACK

