






## **.250 Quick-Connect Series Locking Type**

**— Cross Bridge Design —  
To Accept .250 x .032 Male Tab**

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	18-14	.110-.175	✓ ✓	4000	$\frac{7}{32} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 118A-5
							Brass	3000H 118AB-5
	18-14	None	✓ ✓	5000	$\frac{7}{32} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 118A-5-2
							Brass	3000H 118AB-5-2

## **.250 Quick-Connect Series Locking Type**

**— Closed Back Design —  
To Accept .250 x .032 Male Tab**

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	22-18	.075-.125	— —	3000	$\frac{7}{32} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 111A-6*
							Brass	3000H 111AB-6*
	22-18	.075-.125	— —	3000	$\frac{7}{32} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 112A-6*
							Brass	3000H 112AB-6*
	22-16	None	— —	3000	$\frac{3}{16} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 114A-4A-2*
							Brass	3000H 114AB-4A-2*

\* Less Detent Bump