SM851A1211S MICROSONIC THRU BEAM RECEIVER

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 338.00 USD



Main

Main		
Range of product	Hyde Park	
Sensor type	Ultrasonic sensor	
Series name	Standard format	
Device short name	SM851	
Sensor design	Cylindrical Ø 12 mm plain	
Material	Stainless steel	
[Us] rated supply voltage	1224 V DC	
Electrical connection	1 connector micro	
[Sd] sensing range	0.305 m	
IP degree of protection	IP67	

Complementary

Type of sensing window Fixed	.5
	latarr-
Condition of use Thru beam	for c

Environment

Product certifications CE	

Ordering and shipping details

Complementary		
[Sn] nominal sensing distance	0.305 m	
Type of sensing window	Fixed	
Condition of use	Thru beam	
Environment		
Product certifications	CE	
Ordering and shipping detai	ils	
Category	22490 - SENSORS-ULTRASONIC (XX5,6)	
Discount Schedule	DS2	
GTIN	003389119111645	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.12	
Returnability	Y	
Country of origin	US	
Offer Sustainability		

Offer Sustainability



Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

18 months

Contractual warranty

Warranty period

Life Is On Schneider