



UNLESS OTHERWISE SPECIFIED:
 1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
 3 PLACE DECIMALS ± .004
 T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED HALF THE SUM OF THEIR TOLERANCES.

2. REMOVE ALL BURRS, BREAK SHARP EDGES .005 MAX.
 3. NO FILLETS PERMITTED.
 4. SURFACE ROUGHNESS 63 MICRONS INCHES RMS MAX.
 5. ALL DIMENSIONS PRIOR TO PLATING.
 6. ALL PLATING IN ACCORDANCE WITH KER 10004.

NOTES:
 1. FOR USE WITH RG-8, 9, 213 & 214 / U CABLE GROUPS.
 2. FOR CABLING INSTRUCTIONS SEE CD-1022.

KD-39-46

REVISIONS	
ISSUE	CHANGES
4	CN 23/68E GJG 24 MAR 82
5	CN 29623 A REDRAWN AT 12 FEB 88
6	CN 30644 E M.Z.B. 14 MAR. 89

S=D

SCALE 4:1

APPROX. SURFACE AREA

USED ON

REF

C JACK

DRAWN AT DATE 12 FEB 88

APPR. *[Signature]* DATE 19 FEB 88

APPR. DATE

KINGS
ELECTRONICS CO. INC.
10000 W. 10TH AVE.
DENVER, CO 80201

KD-39-46