

**.500 Flanged Spade  
14-10-AWG**

**Spade and Ring Series  
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS	
10	.150-.250	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5B3-10		
						Pre Tinned Brass	5B4-10		
1/4	.150-.250	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5B3-12		
						Pre Tinned Brass	5B4-12		
10	None	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5B3-9		
						Pre Tinned Brass	5B4-9		
1/4	None	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5B3-11		
						Pre Tinned Brass	5B4-11		

**.240 Flanged Spade  
Insulation Piercing — 2 Barbs**

**Spade and Ring Series  
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
0	.075-.125	— —	6000	—	.020	Brass	2F1-0	
						Pre Tinned Brass	2F2-0	
2	.075-.125	— —	6000	—	.020	Brass	2F1-2	
						Pre Tinned Brass	2F2-2	
4	.075-.125	— —	6000	—	.020	Brass	2F1-4	
						Pre Tinned Brass	2F2-4	