

UniCam® Secure Keyed LC Connector, 62.5 µm multimode (OM1)

Violet

CORNING

Corning secure keyed LC connector solution offers mechanical network security for organisations desiring to segregate networks due to privacy or security concerns. Utilizing the LC small-form-factor (SFF) format for optical fibre cabling, the keyed LC solution provides physical separation for up to eight networks, applications, or organisations. Eight colour-coded key combinations prevent inadvertent or unauthorized access to networks and provide fast and easy network identification. Keyed connectors on the front and back of the patch panel area are used to match access rights to the proper network. The keyed features cannot be duplicated with standard LC components, thereby preventing violation of network security.

Features and Benefits

Eight colour-coded mechanical key positions

Prevents mismatch of networks

Keyed connector solution

Front and rear security in network panel

Broad operating temperature (-40° to +75°C)

Utility and flexibility

Factory-polished end face

Consistent optical performance

Fast termination and no consumables

Low installation cost


Minimum insertion loss

Optimum optical performance

Standards

Approvals and Listings Passed EIA/TIA 568-B.3

Intermateability Connectors are FOCIS compliant with TIA/EIA 604-10A and IEC61754-20



UniCam® Secure Keyed LC Connector, 62.5 µm multimode (OM1)

Violet

CORNING

Specifications

General Specifications	
Technology	No-Epoxy/No-Polish
Keyed	Yes
Product type	Field-Installable Connectors
Corning Logo	Yes
Packaging	Single Pack
Fibre Category	62.5 µm MM (OM1)

Temperature Range	
Operation	-40 °C to 75 °C exceeding EIA/TIA 568-B.3 (-40 °F to 167 °F exceeding EIA/TIA 568-B.3)

Design - Connector	
Connector Type	LC
Ferrule Material	Ceramic
Housing material	Composite
Housing Colour	Violet
Boot colour	Violet

Mechanical Specifications - Connector	
Durability	≤ 0.2 dB change by 500 rematings, FOTP-21
Tensile strength jacketed cable	50 N, change ≤ 0.2 dB, FOTP-6 (11 lb, change ≤ 0.2 dB, FOTP-6)
Tensile strength 900 µm cable	4.9 N, change ≤ 0.2 dB, FOTP-6 (1.1 lb, change ≤ 0.2 dB, FOTP-6)
Nominal fibre outer diameter	125 µm

Optical Specifications - Connector	
Insertion loss, typical	0.3 dB
Insertion Loss, Maximum	0.75 dB
Reflectance	≤ -26 dB

UniCam® Secure Keyed LC Connector, 62.5 μm multimode (OM1)

Violet



Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	-----------------------------------------------------------

Ordering Information

Part Number	95-000-KV
Product Description	UniCam® Secure Keyed LC Connector, 62.5 μm multimode (OM1), ceramic ferrule, single pack, violet housing, violet boot
EAN Code	4056418169989

Shipping Information

Units Per Delivery	1/1
Package Contents	



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.