




ATC



CUSTOM SPECIFICATIONS
AVAILABLE CONTACT FACTORY

STANDARD SPECIFICATIONS

Inductance Range 2 μ H to 1800 μ H
..... contact factory for custom inductance
Operating Temperature Range -25°C to 85°C
Temperature Rise 20°C
Packaging bulk

ATC-100M _____ B _____ Torroid carrier (optional)
_____ Specified Core Material
_____ Tolerance (J=5%, K=10%, M=20%)
_____ Inductance @ 1KHz

ATC PART NUMBER GUIDE

PART NUMBER	Idc (A)	Ind (μ H)	Idc (μ H)	DCR (M Ω)	Dim. (A) (D)	Weight (grams)	PART NUMBER	Idc (A)	Ind (μ H)	Idc (μ H)	DCR (M Ω)	Dim. (A) (D)	Weight (grams)
ATC-5R0M1	0.5	5.0	4.9	35.0	6.0 3.0	0.4	ATC-101M4	5.0	100.0	75.0	31.6	32.0 15.0	39.0
ATC-8R2M1	2.0	8.2	7.2	14.0	12.0 5.0	2.0	ATC-111M1	0.5	110.0	100.0	185.0	12.0 5.0	2.4
ATC-9R0M1	0.3	9.0	8.8	60.0	6.0 2.5	0.2	ATC-111M2	2.0	110.0	79.0	56.0	18.0 10.0	8.0
ATC-100M1	2.0	10.0	7.7	13.0	10.5 5.5	1.6	ATC-111M3	2.0	110.0	90.0	60.0	23.0 9.0	12.0
ATC-120M1	1.0	12.0	10.7	27.0	9.5 5.0	1.2	ATC-111M4	1.0	110.0	56.0	33.0	21.0 9.0	11.4
ATC-150M1	0.5	15.0	13.5	58.0	6.0 3.0	0.4	ATC-131M1	1.0	130.0	116.0	114.0	17.0 8.0	6.4
ATC-150M2	2.0	15.0	12.6	20.5	13.0 6.0	2.8	ATC-131M2	3.0	130.0	77.0	43.0	21.0 9.0	10.6
ATC-200M1	0.2	20.0	19.8	163.0	6.0 2.5	0.2	ATC-131M3	3.0	130.0	96.0	47.1	28.0 12.0	21.0
ATC-200M2	3.0	20.0	15.0	17.6	15.0 7.0	4.4	ATC-131M4	7.0	130.0	79.0	25.0	38.0 16.0	58.0
ATC-220M1	2.0	22.0	17.0	23.0	12.0 6.0	2.4	ATC-141M1	0.5	140.0	107.0	190.0	9.0 4.5	1.2
ATC-220M2	5.0	22.0	15.0	12.0	18.0 10.0	8.0	ATC-141M2	1.0	140.0	104.0	110.0	13.0 6.5	3.2
ATC-240M1	1.0	24.0	22.0	49.5	11.0 5.0	1.6	ATC-141M3	3.0	140.0	98.0	48.5	26.0 12.0	22.0
ATC-250M1	5.0	25.0	18.0	12.8	21.0 8.0	9.2	ATC-151M1	1.0	150.0	137.0	124.0	21.0 8.0	7.6
ATC-270M1	0.1	27.0	27.0	355.0	6.0 2.5	0.2	ATC-151M2	4.0	150.0	110.0	44.0	32.0 15.0	38.4
ATC-270M2	0.3	27.0	25.0	104.5	6.0 3.0	0.2	ATC-151M3	5.0	150.0	68.0	34.5	24.0 11.0	18.0
ATC-290M1	4.0	29.0	20.0	16.0	18.0 10.0	7.8	ATC-201M1	2.0	200.0	154.0	85.0	26.0 12.0	20.8
ATC-300M1	2.0	30.0	25.0	28.5	15.0 7.0	4.0	ATC-201M2	3.0	200.0	157.0	62.0	32.0 15.0	37.8
ATC-300M2	10.0	30.0	21.0	6.3	34.0 17.0	42.0	ATC-201M3	5.0	200.0	134.0	42.7	38.0 15.0	55.6
ATC-320M1	1.0	32.0	25.0	45.0	9.5 5.5	1.4	ATC-221M1	1.0	220.0	162.0	145.0	14.0 7.0	4.4
ATC-320M2	4.0	32.0	24.0	17.2	21.0 8.0	9.0	ATC-221M2	2.0	220.0	170.0	84.5	28.0 12.0	20.6
ATC-350M1	3.0	35.0	28.0	23.0	18.0 9.0	7.6	ATC-221M3	4.0	220.0	105.0	49.0	24.0 11.0	17.9
ATC-350M2	10.0	35.0	25.0	7.4	34.0 17.0	43.0	ATC-231M1	2.0	230.0	148.0	83.3	22.0 9.0	9.8
ATC-370M1	0.5	37.0	33.7	105.0	9.0 4.5	1.0	ATC-241M1	0.5	240.0	190.0	288.0	11.0 5.0	1.6
ATC-430M1	1.0	43.0	37.0	58.0	13.0 5.5	2.6	ATC-251M1	10.0	250.0	105.0	20.0	40.0 20.0	82.0
ATC-430M2	3.0	43.0	34.0	24.0	21.0 8.0	8.8	ATC-271M1	3.0	270.0	140.0	65.5	24.0 11.0	16.6
ATC-500M1	5.0	50.0	33.0	19.0	24.0 10.0	14.2	ATC-301M1	2.0	300.0	250.0	113.0	32.0 15.0	37.8
ATC-560M1	0.5	56.0	53.0	155.0	11.0 5.0	1.4	ATC-301M2	5.0	300.0	120.0	49.2	28.0 13.0	28.8
ATC-560M2	7.0	56.0	41.5	15.5	33.0 16.0	40.0	ATC-321M1	2.0	320.0	193.0	102.0	23.0 10.0	14.0
ATC-580M1	2.0	58.0	45.0	39.0	17.0 8.0	7.2	ATC-321M2	5.0	320.0	120.0	52.2	27.0 14.0	29.6
ATC-600M1	3.0	60.0	35.0	29.6	15.0 9.0	5.8	ATC-361M1	0.5	360.0	285.0	325.0	12.5 5.5	2.8
ATC-600M2	4.0	60.0	42.0	25.0	24.0 10.0	13.7	ATC-391M1	4.0	390.0	165.0	65.7	28.0 12.0	27.2
ATC-650M1	2.0	65.0	55.0	42.8	21.0 8.0	8.2	ATC-431M1	2.0	430.0	246.0	117.5	24.0 11.0	15.0
ATC-680M1	1.0	68.0	53.0	79.0	11.0 5.5	2.0	ATC-451M1	2.0	450.0	280.0	126.0	27.0 13.0	23.0
ATC-680M2	1.0	68.0	60.0	79.4	14.0 6.0	3.6	ATC-471M1	1.0	470.0	310.0	211.0	17.0 8.0	7.6
ATC-680M3	2.0	68.0	42.0	40.0	13.5 7.5	3.8	ATC-471M2	1.0	470.0	398.0	253.0	25.0 11.0	19.5
ATC-680M4	7.0	68.0	46.0	17.2	33.0 16.0	40.0	ATC-471M3	1.0	470.0	400.0	238.0	28.0 12.0	19.0
ATC-750M1	3.0	75.0	54.0	34.0	23.0 10.0	13.0	ATC-471M4	3.0	470.0	225.0	90.5	27.0 14.0	27.0
ATC-750M2	10.0	75.0	43.0	11.3	40.0 17.0	64.0	ATC-471M5	7.0	470.0	190.0	49.0	38.0 18.0	72.0
ATC-820M1	3.0	82.0	60.0	35.0	24.0 10.0	13.0	ATC-501M1	1.0	500.0	355.0	222.0	21.0 9.0	8.6
ATC-820M2	5.0	82.0	52.0	24.4	28.0 12.0	22.4	ATC-501M2	3.0	500.0	242.0	93.5	28.0 13.0	26.0
ATC-820M3	7.0	82.0	53.0	18.9	33.0 16.0	41.0	ATC-681M1	5.0	680.0	295.0	80.4	38.0 17.0	65.2
ATC-900M1	3.0	90.0	52.5	33.2	18.0 10.0	9.2	ATC-781M1	2.0	780.0	428.0	166.3	28.0 12.0	24.1
ATC-900M2	5.0	90.0	54.0	26.1	27.0 13.2	23.6	ATC-851M1	2.0	580.0	567.0	165.5	32.0 16.0	41.8
ATC-101M1	2.0	100.0	63.0	53.6	15.0 8.0	5.2	ATC-961M1	1.0	960.0	625.0	333.0	24.0 10.0	13.0
ATC-101M2	4.0	100.0	69.0	32.5	28.0 12.0	21.9	ATC-132M1	1.0	1300.0	933.0	404.0	28.0 12.0	21.2
ATC-101M3	5.0	100.0	53.0	27.9	24.0 11.0	16.8	ATC-182M1	1.0	1800.0	1130.0	495.0	26.0 12.0	22.4

All specifications subject to change without notice

1010 Calle Cordillera, Building 103 - San Clemente, California 92673

(714) 498-4505 • FAX (714) 498-1714