



OCC1D compact DWDM, 4 channels + upgrade port, single demux, 1561.42 nm starting wavelength, 0.9 mm cable, ruggedized housing

## Product Classification

<b>Product Type</b>	DWDM component
<b>Product Series</b>	OCC1D
<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America

## General Specifications

<b>Distribution Type</b>	4-channel DWDM
<b>Interface, input</b>	Stub tail
<b>Interface, output</b>	Stub tail
<b>Application</b>	For use in FOSC closures
<b>Circuits, quantity</b>	1
<b>Functionality</b>	Demultiplexing
<b>Multiplexers, quantity</b>	1
<b>Package, quantity</b>	1
<b>Port Type, optional</b>	Upgrade port
<b>Technology Type</b>	Thin film filter (TFF)

## Dimensions

<b>Depth</b>	3.97 mm   0.16 in
<b>Height</b>	9.14 mm   0.36 in
<b>Pigtail Diameter</b>	0.90 mm   0.04 in
<b>Pigtail length, input</b>	1.00 m   3.28 ft
<b>Pigtail length, output</b>	1.00 m   3.28 ft
<b>Width</b>	60.96 mm   2.40 in

## Mechanical Specifications

<b>Device Type</b>	Component, rectangular
--------------------	------------------------

## Optical Specifications

**Starting Wavelength** 1560.61 nm  
**Channel Spacing** 100 GHz

## Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant

