





	_	
Parts	Material	Plating (Micro-inch)
Contact Pin	Brass	Gold 20 Over Nickel 50 Over Copper 50
Insulator	Teflon	
Body	Brass	Gold 5 Over Nickel 50 Over Copper 50
Barrel	Brass	Gold 5 Over Nickel 50 Over Copper 50

Weight: 1.42 g

Suitable Cables: Semi-rigid.141

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



CABLE ASSEMBLY INSTRUCTION SMC8300-0141 JYE BAO CO., LTD. Ε Α CONTACT PIN **BODY** *TOOLS AND FIXTURES ARE REFERENCE ON PAGE 306 OF JYEBAO'S 2005 CATALOG. ASSEMBLY INSTRUCTION DIAGRAM 3.7 [.146] Step 1: STRIP AS SHOWN . Е Step 2: PUT 0.2 MM GAGE IN PLACE, INSERT CABLE'S CENTER CONDUCTOR INTO CENTER PIN " E " AND SOLDER IN "Y". GAGE 0.2MM ST-010 Step 3: INSERT PREPARED CABLE INTO SOLDERING FIXTURE "ST-008". USE INSERT TOOL " ST-010 " AND LOCATOR TOOL " ST-011 " TO FIX THE CONNECTOR . SOLDER IN " X " . ST-008 ST-011

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.