






— Axial Bridge Design —
To Accept .250 x .032 Male Tab

.250 Quick-Connect Series Flag Type

WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
20-14	None	✓ ✓	5000	$\frac{5}{16} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 484A	
						Brass	3000H 484AB	
18-14	None	✓ ✓	3000	$\frac{1}{2} \pm \frac{1}{32}$.025	Pre Tinned Brass	3000H 4	
						Brass	3000H 4B	
						Silver Plated Brass	3000H 4H	
18-12	.125-.210	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 68A	
						Brass	3000H 68AB	
						Pre Tinned Phos. Bronze	3000H 68PA	
						Phos. Bronze	3000H 68PB	
						Silver Plated Phos. Bronze	3000H 68PC	
18-12	None	✓ ✓	5000	$1\frac{1}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3000H 4C	
						Brass	3000H 4CB	
						Silver Plated Brass	3000H 4CD	
18-12	None	✓ ✓	5000	$1\frac{1}{32} \pm \frac{1}{32}$.020	Pre-Tinned Brass	3000H 404A*	
						Brass	3000H 404AB*	

* Recommended for Application with CS-21 Auto-Connect System.

S
T
C
E
N
N
O
C
K
I
C
U
Q