


High-Speed CMOS Logic



92CS-38450R1

CD54/74HC4024, HCT4024
FUNCTIONAL DIAGRAM

7-Stage Binary Ripple Counter

Type Features:


- Fully static operation:
- Buffered inputs:
- Common reset
- Typical $f_{MAX} = 50 \text{ MHz} @ V_{CC} = 5 \text{ V}, C_L = 15 \text{ pF}, T_A = 25^\circ \text{ C}$

The RCA-CD54/74HC4024 and CD54/75HCT4024 are 7-stage ripple-carry binary counters. All counter stages are master-slave flip-flops. The state of the stage advances one count on the negative transition of each input pulse; a high voltage level on the MR line resets all counters to their zero state. All inputs and outputs are buffered.

The CD54HC4024 and CD54HCT4024 are supplied in 16-lead hermetic dual-in-line ceramic packages (F suffix). The CD74HC4024 and CD74HCT4024 are supplied in 16-lead dual-in-line plastic packages (E suffix) and in 16-lead dual-in-line surface mount plastic packages (M suffix). Both types are also available in chip form (H suffix).

Family Features:

- Fanout (over temperature range):
Standard outputs - 10 LSTTL loads
Bus driver outputs - 15 LSTTL loads
- Wide operating temperature range:
CD74HC/HCT: -40 to $+85^\circ \text{ C}$
- Balanced propagation delay and transition times
- Significant power reduction compared to LSTTL logic ICs
- Alternate source is Philips/Signetics
- CD54HC/CD74HC types:
2 to 6 V operation
High noise immunity: $N_{IL} = 30\%, N_{IH} = 30\%$ of V_{CC}
 $@ V_{CC} = 5 \text{ V}$
- CD54HCT/CD74HCT types:
4.5 to 5.5 V operation
Direct LSTTL input logic compatibility
 $V_{IL} = 0.8 \text{ V max.}, V_{IH} = 2 \text{ V min.}$
CMOS input compatibility
 $I_i \leq 1 \mu\text{A} @ V_{OL}, V_{OH}$



92CM-38451R3

Fig. 1 - Logic diagram for the CD54/74HC/HCT4024.

TRUTH TABLE

ϕ	MR	OUTPUT STATE
	L	No Change
	L	Advance to Next State
X	H	All Outputs are Low

H = high level (steady state)
L = low level (steady state)
X = don't care

CD54/74HC4024

CD54/74HCT4024

MAXIMUM RATINGS, Absolute-Maximum Values:

DC SUPPLY-VOLTAGE, (V_{CC}):	-0.5 to +7 V
(Voltages referenced to ground)	
DC INPUT DIODE CURRENT, I_{IK} (FOR $V_i < -0.5$ V OR $V_i > V_{CC} + 0.5$ V)	± 20 mA
DC OUTPUT DIODE CURRENT, I_{OK} (FOR $V_o < -0.5$ V OR $V_o > V_{CC} + 0.5$ V)	± 20 mA
DC DRAIN CURRENT, PER OUTPUT (I_o) (FOR -0.5 V $< V_o < V_{CC} + 0.5$ V)	± 25 mA
DC V_{CC} OR GROUND CURRENT, (I_{CC})	± 50 mA
POWER DISSIPATION PER PACKAGE (P_D):		
For $T_A = -40$ to $+60^\circ$ C (PACKAGE TYPE E)	500 mW
For $T_A = +60$ to $+85^\circ$ C (PACKAGE TYPE E)	Derate Linearly at 8 mW/ $^\circ$ C to 300 mW
For $T_A = -55$ to $+100^\circ$ C (PACKAGE TYPE F, H)	500 mW
For $T_A = +100$ to $+125^\circ$ C (PACKAGE TYPE F, H)	Derate Linearly at 8 mW/ $^\circ$ C to 300 mW
For $T_A = -40$ to $+70^\circ$ C (PACKAGE TYPE M)	400 mW
For $T_A = +70$ to $+125^\circ$ C (PACKAGE TYPE M)	Derate Linearly at 6 mW/ $^\circ$ C to 70 mW
OPERATING-TEMPERATURE RANGE (T_A):		
PACKAGE TYPE F, H	-55 to $+125^\circ$ C
PACKAGE TYPE E, M	-40 to $+85^\circ$ C
STORAGE TEMPERATURE (T_{stg})	-65 to $+150^\circ$ C
LEAD TEMPERATURE (DURING SOLDERING):		
At distance 1/16 \pm 1/32 in. (1.59 \pm 0.79 mm) from case for 10 s max.	$+265^\circ$ C
Unit inserted into a PC Board (min. thickness 1/16 in., 1.59 mm) with solder contacting lead tips only	$+300^\circ$ C

RECOMMENDED OPERATING CONDITIONS

For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges:

CHARACTERISTIC	LIMITS		UNITS
	MIN.	MAX.	
Supply-Voltage Range (For T_A =Full Package Temperature Range) V_{CC} *			
CD54/74HC Types	2	6	V
CD54/74HCT Types	4.5	5.5	V
DC Input or Output Voltage, V_i, V_o	0	V_{CC}	V
Operating Temperature, T_A :			
CD74 Types	-40	+85	$^\circ$ C
CD54 Types	-55	+125	$^\circ$ C
Input Rise and Fall Times, t_r, t_f :			
at 2 V	0	1000	ns
at 4.5 V	0	500	
at 6 V	0	400	

*Unless otherwise specified, all voltages are referenced to Ground.




Fig. 2 - Flip-flop No. 1 detail.




Fig. 3 - Detail for flip-flops 2 through 7.

CD54/74HC4024

CD54/74HCT4024

 SWITCHING CHARACTERISTICS ($V_{CC}=5\text{ V}$, $T_A=25^\circ\text{ C}$, Input $t_r, t_f=6\text{ ns}$)

CHARACTERISTIC	SYMBOL	C_L (pF)	TYPICAL VALUES		UNITS
			HC	HCT	
Propagation Delay ϕ to Q_1'	t_{PHL}	15	11	17	ns
	t_{PLH}				
Q_n to Q_{n+1}	t_{PHL}	15	6	6	
MR to Q_n	t_{PHL}	15	14	17	ns
	t_{PLH}				
Power Dissipation Capacitance*	C_{PD}	—	30	30	pF

 * C_{PD} is used to determine the dynamic power consumption, per package.

 $P_D = C_{PD} V_{CC}^2 f_i + \sum (C_L V_{CC}^2 f_i/M)$ where:

 $M=2^1, 2^2, 2^3, 2^4, 2^5, 2^6, 2^7$
 C_L =output load capacitance

 f_i =input frequency



Prerequisite for Switching Function

CHARACTERISTIC	SYMBOL	V_{CC}	25°C		-40°C to +85°C				-55°C to +125°C				UNITS		
			HC		HCT		74HC		74HCT		54HC			54HCT	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.		Min.	Max.
Maximum Input Pulse Frequency	f_{MAX}	2	6	—	—	—	5	—	—	—	4	—	—	—	MHz
		4.5	30	—	25	—	24	—	20	—	20	—	16	—	
		6	35	—	—	—	29	—	—	—	24	—	—	—	
Input Pulse Width	t_W	2	80	—	—	—	100	—	—	—	120	—	—	—	ns
		4.5	16	—	20	—	20	—	25	—	24	—	30	—	
		6	14	—	—	—	17	—	—	—	20	—	—	—	
Reset Removal Time	t_{REM}	2	50	—	—	—	65	—	—	—	75	—	—	—	ns
		4.5	10	—	10	—	13	—	13	—	15	—	15	—	
		6	9	—	—	—	11	—	—	—	13	—	—	—	
Reset Pulse Width	t_W	2	80	—	—	—	100	—	—	—	120	—	—	—	ns
		4.5	16	—	20	—	20	—	25	—	24	—	30	—	
		6	14	—	—	—	17	—	—	—	20	—	—	—	

 SWITCHING CHARACTERISTICS ($C_L=50\text{ pF}$, Input $t_r, t_f=6\text{ ns}$)

CHARACTERISTIC	SYMBOL	V_{CC}	25°C				-40°C to +85°C				-55°C to +125°C				UNITS
			HC		HCT		74HC		74HCT		54HC		54HCT		
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
Propagation Delay, ϕ to Q_1' Output	t_{PLH}	2	—	140	—	—	—	175	—	—	—	210	—	—	ns
		4.5	—	28	—	40	—	35	—	50	—	42	—	60	
		6	—	24	—	—	—	30	—	—	—	36	—	—	
Propagation Delay Q_n to Q_{n+1}	t_{PHL}	2	—	75	—	—	—	95	—	—	—	110	—	—	ns
		4.5	—	15	—	15	—	19	—	19	—	22	—	22	
		6	—	13	—	—	—	13	—	—	—	19	—	—	
Propagation Delay MR to Q_n	t_{PHL}	2	—	170	—	—	—	215	—	—	—	255	—	—	ns
		4.5	—	34	—	40	—	43	—	50	—	51	—	60	
		6	—	29	—	—	—	27	—	—	—	43	—	—	
Output Transition Time	t_{TLH}	2	—	75	—	—	—	95	—	—	—	110	—	—	ns
		4.5	—	15	—	15	—	19	—	19	—	22	—	22	
		6	—	13	—	—	—	16	—	—	—	19	—	—	
Input Capacitance	C_i	—	—	10	—	10	—	10	—	10	—	10	—	pF	

CD54/74HC4024 CD54/74HCT4024



	54/74HC	54/74HCT
Input Level	V _{CC}	3 V
Switching Voltage, V _S	50% V _{CC}	1.3 V

Fig. 4 - Input Pulse pre-requisite times, propagation delays and output transition times.

Fig. 5 - Master Reset pre-requisite and propagation delays.

