

# .250 Quick-Connect Series

## In-Line Type

— Axial Bridge Design —  
 To Accept .250 x .032 Male Tab

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	22-18	.040-.090	✓ ✓	6000	$\frac{7}{32} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 219A-6
							Brass	3000H 219AB-6
	22-18	None	✓ ✓	6000	$\frac{7}{32} \pm \frac{1}{32}$	.016	Pre Tinned Brass	3000H 219A-6-2
							Brass	3000H 219AB-6-2
	22-18	.040-.090	✓ ✓	4000	$\frac{7}{32} \pm \frac{1}{32}$	.020	Pre Tinned Brass	3000H 19A-6
							Brass	3000H 19AB-6
	22-18	None	✓ ✓	4000	$\frac{7}{32} \pm \frac{1}{32}$	.020	Pre Tinned Brass	3000H 19A-6-2
							Brass	3000H 19AB-6-2
	22-18	.040-.090	✓ ✓	4000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Pre Tinned Brass	3000H 20A
							Brass	3000H 20AB
							Silver Plated Brass	3000H 20AC
	22-18	None	✓ ✓	5000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Pre Tinned Brass	3000H 20A-2
							Brass	3000H 20AB-2
							Silver Plated Brass	3000H 20AC-2

Note: The Above Series will Accept #24-#18 AWG.