

SPECIFICATIONS:

Dielectric Withstanding : 600V RMS.
 Contact Resistance: 100Milliohms Max.
 Insulation Resistance : 5000 Megohms Min.
 Temperature : -55°C To +125°C
 Insertion Force : Average 500 GR
 Extraction Test : Average 159 GR
 Resist To Soldering Heat: Max. 260°C,5 Sec.
 Contact Plating : Gold Flash

Poles	A	B	C
06	7.62	7.62	10.16
08	10.16	7.62	10.16
10	12.70	7.62	10.16
14	17.78	7.62	10.16
16	20.32	7.62	10.16
18	22.86	7.62	10.16
20	25.40	7.62	10.16
22	27.94	7.62	10.16
24	30.48	7.62	10.16
26	35.56	7.62	10.16


AUK A NUMBER OF AUK GROUP
 太聯事業股份有限公司
 AUK CONTRACTORS CO., LTD.

DRAWING No.
 SIC0310

APPROVED BY
 MEI
 CHECKED BY
 RAN
 DRAWING BY
 HZF

UNLESS OTHERWISE SPECIFIED
 TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 AWG.

SCALE NONE REV. A UNIT mm



AREA REVISIONS CHK DATE