

ABSORPTIVE SWITCHES

Frequency* Range (GHz)	Switch Type	Insertion Loss (dB) max.	Isolation (dB) min.	VSWR max.	Supply Requirements		P/N
					mA +5V dc	mA -5V dc	
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP1T	1.6 1.8 2.8	60	1.90:1	70	70	SW1AD-01
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP1T	1.6 1.8 2.8	60 60 50	1.90:1	70	70	SW1AD-02
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP2T	1.7 1.9 3.1	60	1.90:1 1.90:1 2.00:1	80	70	SW2AD-01
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP2T	1.7 1.9 3.1	60 60 50	1.90:1 1.90:1 2.00:1	80	70	SW2AD-02
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP3T	2.0 2.2 3.4	60	1.90:1 1.90:1 2.00:1	120	70	SW3AD-01
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP3T	2.0 2.2 3.4	60 60 50	1.90:1 1.90:1 2.00:1	120	70	SW3AD-02
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP4T	1.9 2.5 3.5	60 60 50	2.00:1	150	100	SW4AD-01
0.01 - 2.5 0.01 - 2.5 0.01 - 2.5	SP1T SP2T SP3T	0.5 1.0 1.5	60	2.00:1	70 100 120	50 70 70	SW1L-01 SW2L-01 SW3L-01

* Other frequency bands available, consult factory.
See outlines on page 76.