

TSRK10/ZP

- 1 Connection



Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	10.0 mm ²	Flammability Class	UL 94 V-0
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	10.0 mm ²	Working Temperature	-40 - 120 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	10.0 mm ²	Stripped Length	12.0 mm
Clamping Range min	0.2mm ²	Width	15.0 mm
Clamping Range max	10.0 mm ²	Height	41.0 mm
		Length	40.5 mm

Colours

- ORANGE, similar RAL 2003
- BEIGE, similar RAL 1019

Connection Diagram



Order Data

Article Designation	Article Number	PU
TSRK10/ZP-ORANGE	41161.3	50
TSRK10/ZP-BEIGE	41161.2	50

Accessoires

Article Designation	Article Number	PU
Quick Labelling PSB7.5/40	499326.7	400
Quick Labelling PSB7.5/40-B	493327.7	400

Ratings

Ratings	CSA	CSAus	IEC
Rated Voltage	600 V	600 V	800 V
Rated Current	65 A	65 A	57 A
Rated Wire Size	AWG 22-10	AWG 22-10	10.0 mm ²
Rated Impulse Voltage			8 V
Pollution Degree			3