




0.7" 5x7 DOT MATRIX DISPLAYS

HER GMA 7175C GMC 7175C
YELLOW GMA 7475C GMC 7475C
GREEN GMA 7975C GMC 7975C

PACKAGE DIMENSIONS



ST2618

NOTES:

1. ALL PINS ARE 90.5 (.02).
2. DIMENSION IN MILLIMETERS (INCH). TOLERANCE IS 0.25 (.01) UNLESS OTHERWISE NOTED.

DESCRIPTION

The GMX7X75C series are 0.7" (17.2mm) matrix height 5 X 7 dot matrix displays. All these parts are available in grey face and white dot color.

The X in GMX denotes row anode or row cathode.

FEATURES

- 0.7" (17.8mm) matrix height
- Choice of 3 colors --- green, yellow and HER
- Low power consumption
- 5x7 array with X-Y select
- Stackable vertically and horizontally
- Choice of 2 matrix orientation cathode column or anode column
- Easy mounting on PCB or sockets
- Categorized for luminous intensity


ABSOLUTE MAXIMUM RATING ($T_c = 25^\circ\text{C}$ unless otherwise specified)

	YELLOW	HER	GREEN	UNITS
Power dissipation per dot	60	70	75	mW
Peak forward current per dot	80	100	100	mA
(Duty cycle 1/10, 10KHz)				
Continuous I_f per dot	20	25	25	mA
Reverse voltage per dot	5	5	5	V
Operating and operating temperature range				-25°C to $+85^\circ\text{C}$
Soldering time at 260°C (1/16 inch below seating plane)				3 sec

ELECTRICAL/OPTICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ Unless otherwise specified)
GMX 7175C (HER)


PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Average luminous intensity		3000		μcd	$I_f = 20\text{ mA}$
Peak emission wavelength		635		nm	$I_f = 20\text{ mA}$
Spectral line half-width		40		nm	$I_f = 20\text{ mA}$
Forward voltage, any dot		2.1	2.8	V	$I_f = 20\text{ mA}$
Reverse voltage, any dot			100	μA	$V_r = 5\text{V}$

TYPICAL ELECTRICAL/OPTICAL CHARACTERISTIC CURVES
($T_c = 25^\circ\text{C}$ Unless otherwise specified)




C3031

Fig. 1. Forward Current vs. Forward Voltage




C3032

Fig. 2. Spectral Response




C3033

Fig. 3. Relative Luminous Intensity vs. Forward Current (Per Segment)




C3034

Fig. 4. Max. Forward Allowable DC Current Per Seg. vs. Ambient Temperature



C3035

Fig. 5. Max. Peak Current vs. Duty Cycle % (Refresh Rate - $F = 1\text{ KHz}$)





C3036

Fig. 6. Luminous Intensity vs. Duty Cycle % (Average $I = 10\text{ mA}$ Per Seg.)



ELECTRICAL/OPTICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ Unless otherwise specified)					
GMX 7475C (YELLOW)					
PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Average luminous intensity		3000		μcd	$I_f = 20\text{ mA}$
Peak emission wavelength		585		nm	$I_f = 20\text{ mA}$
Spectral line half-width		35		nm	$I_f = 20\text{ mA}$
Forward voltage, any dot		2.1	2.8	V	$I_f = 20\text{ mA}$
Reverse voltage, any dot			100	μA	$V_R = 5\text{V}$

TYPICAL ELECTRICAL/OPTICAL CHARACTERISTIC CURVES
($T_c = 25^\circ\text{C}$ Unless Otherwise Noted)



ELECTRICAL/OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise specified)					
GMX 7975C (GREEN)					
PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Average luminous intensity		3000		μcd	$I_f = 20\text{ mA}$
Peak emission wavelength		565		nm	$I_f = 20\text{ mA}$
Spectral line half-width		30		nm	$I_f = 20\text{ mA}$
Forward voltage, any dot		2.1	2.8	V	$I_f = 20\text{ mA}$
Reverse voltage, any dot			100	μA	$V_R = 5\text{V}$

TYPICAL ELECTRICAL/OPTICAL CHARACTERISTIC CURVES
($T_A = 25^\circ\text{C}$ Unless otherwise specified)





**0.7" 5x7
DOT MATRIX DISPLAYS**

PIN CONNECTION		
PIN NO.	GMA7X75C	GMC7X75C
1	Anode row 1	Cathode row 1
2	Anode row 2	Cathode row 2
3	Cathode column 2	Anode column 2
4	Cathode column 1	Anode column 1
5	Anode row 6	Cathode row 6
6	Anode row 7	Cathode row 7
7	Cathode column 3	Anode column 3
8	Anode row 5	Cathode row 5
9	Cathode column 4	Anode column 4
10	Anode row 4	Cathode row 4
11	Cathode row 3	Anode row 3
12	Cathode row 5	Anode row 5

