



- NOTE:
- This product is enable to mount both US3-IF Recommended PCB pattern bottom of soldering terminals
 - Compatibility : The dimension between flat lead and when connector put on the flat lead like PCB Signal Connector Ter' solder tail : Max 0.08 mm Metal tab : Max 0.1mm
 - PRODUCT NUMBERING:
1010411 - 0001 LF
 - The "LF" is meant lead free and can withstand expose to 250° C peak temperature for 10 seconds in its reflow process.

mat'l. code	tolerances unless otherwise specified	CUSTOMER COPY	FCI
litr	ecn no	dr	date
A	T10-0002	J.H	1/7/10
B	T10-0063	J.H	5/12/10
C	T11-0016	J.H	3/16/11
D	ELX-N-1600	J.H	10/21/13
E	ELX-N-17563	dr	4/24/13
F	ELX-N-19383	chr	11/18/14
G	ELX-N-22385	LA	10/28/15
Sheet index	revision	Sheet	revision
1	D	1	

ITEM	DESCRIPTION	MATERIAL	FINISH	QTY
1	HOUSING	THERMOPLASTIC-GF	GRAY	1
2	CONTACT	COPPER ALLOY	PLATING : Sn ²⁺ Au PLATED OVER NICKEL OVERALL	5
3	SHELL	STAINLESS STEEL	PLATING : TIN OVER NICKEL OVERALL	1

projection	scale	product family	code
5:1	MM	USB	10104111
sheet	revision	code	sheet
1	D	TWN	1 of 1

title MICRO USB A/B TYPE RECEPTACLE
product family USB
size: dwg no 10104111
www.fciconnect.com