



SPECIFICATIONS

- Voltage Withstanding : AC 1000V For 1 Minute
- Insulation Resistance: 300MΩ Min At 500V DC
- Contact Resistance : 20 Milliohms Max.
- Insertion Force : 6.5 Kg Max.
- Withdrawal Force : 1-5Kg
- 1-Socket Case : SPCC-SD 0.4t,Nickel Plated
- 2-Insulator : P.B.T,UL 94V-0
- 3-Earth Terminal : Pbsr-H 0.25t,Pb10%,Sn 90%
- 4-Contact Terminal : Brass 0.7t,Pb 10%. Sn 90%
- 5-Rivet : AL ,Nickel Plated

Recommended PCB Layout
[TOP VIEW]

Arrangement Of Contacts	72°	60°	45°	45°
Pin No.	04	06	07	08
Hole Layout				

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY Din Jack		APPROVED BY MEI	
PART No. DJXXD		CHECKED BY RAN	
DRAWING No. DJXXD		DRAWING BY LXH	
SCALE NONE	REV. A1	UNIT mm	

UNLESS OTHERWISE SPECIFIED
 TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 AWG.

△ A1	Del Drawing:Pin No.5	BECKY	2004/06/03
△ A1	Modify Spec.1-3.5kg - 1-5kg	BECKY	2004/06/03
△ A1	Modify Spec.4.0kg - 6.5kg	BECKY	2004/06/03
△ A1	Add Drawing	BECKY	2004/06/03
△ A0	NEW RELEASE		
NO. REV.	REVISIONS	CHK	DATE