






Specialty Terminals

Specialty Contacts and Connectors

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	20-18 or (2) 20's	.075-.175	3000	$\frac{5}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3800M 11A
	22-18	—	3000	$\frac{5}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass Brass	3800S 111A 3800S 111AB
	<u>20-18</u> <u>20-14</u> 16-12	—	3000	$\frac{3}{16} \pm \frac{1}{32}$.032	Pre Tinned Brass Brass Pre Tinned Brass Brass Pre Tinned Brass Brass	3800S 94A-6 3800S 94AB-6 3800S 94A 3800S 94AB 3800S 94A-7 3800S 94AB-7
	<u>20-18</u> <u>20-14</u>	—	3000	$\frac{3}{16} \pm \frac{1}{32}$.032	Pre Tinned Brass Brass Pre Tinned Brass Brass	3800S 112A-6 3800S 112AB-6 3800S 112A 3800S 112AB
	20-16	.100-.155	3500	$\frac{5}{32} \pm \frac{1}{32}$.016	Phosphor Bronze	3800H 54AB