



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. BRASS PER QQ-B-613  
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN THICK OVER COPPER STRIKE  
 4. BERYLLIUM COPPER PER QQ-C-530  
 5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 6. TEFLON MIL-P-19468

1. CRIMPED FERRULE  
 HEX CRIMP SIZE .128"  
 2. MAX. PANEL THICKNESS=3mm

7	FERRULE	COPPER	NOTE 3	1	FR-38/3X7C
6	HEX NUT	NOTE 1	NOTE 3	1	HN635-10-56X15
5	LOCK WASHER	NOTE 2	NOTE 3	1	LW-78/5X05
4	CONTACT PIN	NOTE 4	NOTE 5	1	MMCX6121A1-4-085/06
3	BARREL	NOTE 1	NOTE 3	1	MMCX1121A1-3-23/17
2	INSULATOR	NOTE 6	NATURAL	1	MMCX6121A1-2T-316U
1	BODY	NOTE 1	NOTE 3	1	MMCX6421A1-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO. MMCX6421A1-3GT30G-5-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED	DATE 10-11-01'
0.5-6	= ±0.2		CHECKED	DATE 10-11-01'
6-30	= ±0.4		DRAWN	DATE 10-11-01'
30-120	= ±0.6			
120-315	= ±1			
315-1000	= ±1.6			
1000-2000	= ±2.4			
SCALE	6/1	ISSUE	A	FILE NO.

<b>Amphenol</b>	
TITLE MMCX BULKHEAD CRIMP JACK (FOR RG-174/U,188A/U,316/U)	
DRAWING NO. KJ-MMCX6421A1-3GT30G-316U-50	
ITEM NO.	