



Our commitment. Your advantage.

 Search

- [Products](#)
- [Documentation](#)
- [Resources](#)
- [My Account](#)
- [Customer Support](#)

[Home](#) > [Products](#) > [By Type](#) > [Single Fiber/Duplex Products](#) > [Product Feature Selector](#) > Product Details

## 504015-9 Product Details



### FSMA Connectors

[Not reviewed for RoHS Compliance](#)

#### Product Highlights:

- Connector
- Connector Type = FSMA II (906 Style)
- Jacket Outer Diameter = 4.30 mm
- Fiber Size = 125 Micron
- Packaging Method = Loose Piece

[View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**504015-9**

TE Internal Number: 504015-9



- [Add to My Part List](#)
- [Request Sample](#)
- [Find Similar Products](#)
- [Buy Product](#)

[Contact Product Information Center](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">OPTIMATE FSMA Fiber Optic Connector Types 905 and 906</a> (PDF, English)</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Type</a> = Connector</li> <li>• <a href="#">Connector Type</a> = FSMA II (906 Style)</li> <li>• Body Material = Brass</li> </ul> <p><b>Termination Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Fiber Size (Micron)</a> = 125</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Jacket Outer Diameter (mm [in])</a> = 4.30 [0.169]</li> <li>• Assembly Length (mm [in]) = 68.86 [2.710]</li> <li>• Ferrule Material = Ceramic</li> <li>• Body Plating = Nickel</li> </ul>	<p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = Not reviewed for ELV/RoHS compliance</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not reviewed for lead free solder process</li> </ul> <p><b>Packaging Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Packaging Method</a> = Loose Piece</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = AMP</li> </ul>

[Provide Website Feedback](#) | [Need Help?](#)