

# In-Line Optical Attenuators, Flat Wavelength, ST<sup>®</sup> Compatible UPC

ST<sup>®</sup> Compatible UPC, 7 dB

CORNING

Corning offers in-Line, flat wavelength optical attenuators that are easily inserted between the connector and adapter in an “in-line” configuration and are compatible with SC, ST<sup>®</sup> compatible, FC, MU, LC and angled SC and FC connectors. A fundamental element of these Corning attenuators is the zirconia ferrule containing a specially selected attenuating fiber. This special fiber minimizes the effect of modal interference and gives the component a flat spectral response. It is extremely stable over the wavelength range of 1260 to 1360 nm and 1430 to 1580 nm. These in-line, flat wavelength attenuators are available in ultra PC ( $\leq$  -55 dB) and angled PC ( $\leq$  -65 dB) finish to meet the most demanding network reflectance requirements.

## Features and Benefits

**Fully compatible with ST<sup>®</sup> Compatible fiber optic connectors**

No intermateability concerns

**Numerical identification mark on housing**

Easy indication of attenuation levels

**Attenuator incorporated inside standard ST<sup>®</sup> Compatible adapter housings**

Compatible with standard distribution panels

## Standards

**Design and Test Criteria** Telcordia GR-910 issue 2 performance requirements



Part Number: ATN-61-07



Part Number: ATN-61-07

CORNING

# In-Line Optical Attenuators, Flat Wavelength, ST<sup>®</sup> Compatible UPC

ST<sup>®</sup> Compatible UPC, 7 dB

CORNING

## Specifications

### General Specifications

Attenuator Type	In-Line
Compatibility	ST <sup>®</sup> Compatible
Packaging	Single Pack
Product Type	Attenuators

### Temperature Range

Operation	-25 °C to 70 °C (-13 °F to 158 °F)
-----------	------------------------------------

### Design - Connector

Ferrule Material	Zirconia
Housing Material	Metal
Housing Color	Metal

### Optical Specifications - Connector

Attenuation	7 dB
Attenuation Tolerance	± 0.7 dB
Insertion Loss	0.07 dB

### Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Ordering Information

Part Number	ATN-61-07
Product Description	ST <sup>®</sup> Compatible UPC In-Line Optical Attenuator, Flat Wavelength
EAN Code	4056418195421

# In-Line Optical Attenuators, Flat Wavelength, ST® Compatible UPC

ST® Compatible UPC, 7 dB

CORNING

## Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, ST® Compatible



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks).

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING