


# Spade and Ring Series Pre-Insulated

.380 Square Spade  
.031 Electro-Tinned Copper  
22-18 AWG (Red)


G  
N  
I  
R  
&

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER		
		.117	.147	.180							
	6	X			B	✓	✓	5000	50483		
				X		B	✓	✓	4000	50483-8	
					X		B	✓	*	4000	50483-8A
		X				W	✓	✓	5000	50484	
				X		W	✓	✓	4000	50484-8	
					X	W	✓	*	4000	50484-8A	
	8	X				B	✓	✓	5000	50495	
				X		B	✓	✓	4000	50495-8	
					X	B	✓	*	4000	50495-8A	
		X				W	✓	✓	5000	50496	
				X		W	✓	✓	4000	50496-8	
					X	W	✓	*	4000	50496-8A	
10	X				B	✓	✓	5000	50507		
			X		B	✓	✓	4000	50507-8		
				X	B	✓	*	4000	50507-8A		
	X				W	✓	✓	5000	50508		
			X		W	✓	✓	4000	50508-8		
				X	W	✓	*	4000	50508-8A		

# Spade and Ring Series Pre-Insulated

.500 Square Spade  
.031 Electro-Tinned Copper  
22-18 AWG (Red)

E  
D  
A  
P  
S

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER		
		.117	.147	.180							
	10	X			B	✓	✓	5000	50687		
				X		B	✓	✓	4000	50687-8	
					X		B	✓	*	4000	50687-8A
		X				W	✓	✓	5000	50688	
				X		W	✓	✓	4000	50688-8	
					X	W	✓	*	4000	50688-8A	
	1/4	X				B	✓	✓	5000	50699	
				X		B	✓	✓	4000	50699-8	
					X	B	✓	*	4000	50699-8A	
		X				W	✓	✓	5000	50700	
				X		W	✓	✓	4000	50700-8	
					X	W	✓	*	4000	50700-8A	

Recommended Strip Length  $\frac{3}{32} \pm \frac{1}{32}$   
\* Contact Factory for Latest Agency Approvals.