

TYPES YSS, YCS-R & YDS-AT

HYSPLICE™

For Aluminum, ACSR, 6201, 5005 and Compressed.



Single aluminum sleeve designed for service drop or short span overhead distribution lines. Installed with OH25 one-hand tool, and other standard tooling. Pre-filled with PENETROX™ joint compound and color coded capped.

CATALOG NUMBER	CONDUCTOR	L	HOLDING STRENGTH LBS.	DIE INDEX	COLOR CODE	TOOLS, DIE SETS CATALOG NUMBER, & (CRIMPS PER END)		OH25 APPLICATIONS	
						MD7, MD6	Y35, Y750, Y45†, Y46‡	CONDUCTOR	OH25 (INDENTS PER END)
YSS6RG2	6 ACSR 4 Sol. Al	4-1/8	900 700	BG or 5/8	Blue	BG (6) W-BG (3)*	U-BG (3)*	—	—
YSS6R	4 Sol. Al	4-3/4	900 700	162	Blue	W162 (4)	U162 (2)*	—	—
YDS4WA YDS4CA	4 Sol. Al 4 Str. Al (7)	2-5/8	750** 700**	162	Orange	W162 (4)	U162 (1)*	—	—
YSS4R	4 ACSR	4-1/8	1000	BG or 5/8	Orange	BG (6) W-BG (3)*	U-BG (3)*	4 7 Al	(3)
	2 Sol. Al		800					4 5005 Al	(2)
	2 Al (7)		700					4 5005 Al	(3)
YSS2R	2 ACSR	4-1/8	1600	Red	Red	BG (6) W-BG (3)*	U-BG (3)*	4 (6-1) ACSR	(3)
	2 Al (7)		1200					4 (6-1) ACSR	(2)
YDS25AT	1/0 Al (7)	7-1/4	2000	BG, 5/8 or 243	Yellow	BG (12) W-BG (6)*	U-BG (6)*	1/0 7 Al	(4)
YCS25R	1/0 ACSR	7-1/8	2320	BG, 5/8 or 243	Yellow	BG (12) W-BG (6)*	U-BG (6)*	1/0 (6-1) ACSR	(2)
								1/0 (6-1) ACSR	(3)

E-47

* Multiple crimp die set; makes more than one crimp per tool compression. Figure indicates number of compressions.

** Holding strength values up to 800 lbs. are obtained when HYPRESS™ tools are used for installations.

† U Die with adapter PT-6515

‡ U Die with adapter PUADP-1.