


HIGH FREQUENCY NPN TRANSISTOR IN A HERMETICALLY SEALED CERAMIC SURFACE MOUNT PACKAGE FOR HIGH RELIABILITY APPLICATIONS

MECHANICAL DATA
Dimensions in mm (inches)



FEATURES

- SILICON NPN TRANSISTOR
- HERMETIC CERAMIC SURFACE MOUNT PACKAGE (SOT23 COMPATIBLE)
- CECC SCREENING OPTIONS

**SOT23 CERAMIC
(LCC1 PACKAGE)**

Underside View

PAD 1 – Base PAD 2 – Emitter PAD 3 – Collector

APPLICATIONS:

Hermetically sealed surface mount version of the popular 2N2857 for high reliability applications requiring small size and low weight devices.

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise stated)

V_{CBO}	Collector – Base Voltage	30V
V_{CEO}	Collector – Emitter Voltage	15V
V_{EBO}	Emitter – Base Voltage	2.5V
I_C	Collector Current	40mA
P_D	Total Device Dissipation @ $T_A = 25^\circ\text{C}$	200mW
	Derate above 25°C	1.14mW / °C
P_D	Total Device Dissipation @ $T_C = 25^\circ\text{C}$	300mW
	Derate above 25°C	1.72mW / °C
T_{STG}, T_J	Operating and Storage Temperature Range	-65 to +200°C

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise stated)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{(BR)CBO}^*$ Collector – Base Breakdown Voltage	$I_C = 1\mu\text{A}$ $I_E = 0$	30			V
$V_{(BR)CEO}$ Collector – Emitter Breakdown Voltage	$I_C = 3\text{mA}$ $I_B = 0$	15			
$V_{(BR)EBO}$ Emitter – Base Breakdown Voltage	$I_E = 10\mu\text{A}$ $I_C = 0$	2.5			
I_{CBO} Collector – Base Cut-off Current	$V_{CB} = 15\text{V}$ $I_E = 0$			50	μA
	$T_A = -55^\circ\text{C}$			1	
$V_{CE(sat)}$ Collector – Emitter Saturation Voltage	$I_C = 10\text{mA}$			0.4	V
$V_{BE(sat)}$ Base – Emitter Saturation Voltage	$I_B = 1\text{mA}$	0.5		1	
h_{FE} DC Current Gain	$V_{CE} = 1\text{V}$ $I_C = 3\text{mA}$	30		150	—
	$T_A = 150^\circ\text{C}$	10			
I_{CES} Collector – Emitter Cut-off Current	$V_{CB} = 16\text{V}$ $I_B = 0$			100	nA
NF Noise Figure	$V_{CE} = 6\text{V}$ $I_C = 1.5\text{mA}$ $f = 450\text{MHz}$ $R_G = 50\Omega$			4.5	dB
h_{fe} Small Signal Current Gain	$V_{CE} = 6\text{V}$ $I_C = 2\text{mA}$ $F=1\text{KHz}$	50		220	—
$ h_{fe} $ Magnitude of h_{fe}	$V_{CE} = 6\text{V}$ $I_C = 5\text{mA}$ $f = 100\text{MHz}$	10		21	—
C_{cb} Collector – Base Feedback Capacitance	$V_{CB} = 10\text{V}$ $I_E = 0$ $f = 0.1$ to 1MHz			1	pF
G_{pe} Small Signal Power Gain	$V_{CE} = 6\text{V}$ $I_C = 1.50\text{mA}$ $f = 450\text{MHz}$	12.5		21	dB
$r_b'C_c$ Collector – Base Time Constant	$V_{CE} = 6\text{V}$ $I_E = 2\text{mA}$ $f = 31.9\text{MHz}$	4.0		15	ps

--	--	--

Part number search for devices beginning "2N2857CSM"

[Semelab Home](#)

Datasheets are downloaded as Acrobat PDF files.



Bipolar Products

PRODUCT	Polarity	Package	V _{CEO}	I _{C(cont)}	H _{FE(min)}	H _{FE(max)}	@ V _{CE} /I _C	F _T	P _D
2N2857CSM	NPN	LCC1	30V	0.04A	-	-	-	1.9GHz	0.2W
2N2857CSM-JQR-B	NPN	LCC1	30V	0.04A	-	-	-	1.9GHz	0.2W

Searched through 3084 records and found 2 products matching your criteria.

[Top of Page](#)

If you are unable to find a suitable part, please [contact us](#).

