

HA166152FP4

Pre Amplifier for Hard Disk Drive

HITACHI

Rev. 0
Oct. 1993

The HA166152FP4 is read/write amplifier designed for use with thin film recording heads. They have the following functions and features.

Functions

- Read amplifier circuit
- Write driver circuit
- Constant write current setup circuit
- 4 channel servo write

Features

- Single power supply +5 V
- Low power
 - Read: 195 mW (Typ)
 - Idle: 35 mW (Typ)
- Low Noise: 0.5 nV/ $\sqrt{\text{Hz}}$ (Typ)
- Read amplifier has high differential voltage gain : 345 V/V (Typ)
- Built-in current and voltage monitors
- ECL compatible interface
- Emitter-follower read amplifier outputs
- Input capacitance: 10 pF (Typ)
- Write current range: 5 to 30 mA

Ordering Information

Type	Channel	Package
HA166152FP4	4	FP-20DA

Pin Arrangement

GND	1	20	$\overline{\text{CS}}$
H0X	2	19	R/W
H0Y	3	18	WC
H1X	4	17	RDY
H1Y	5	16	RDX
H2X	6	15	HS0
H2Y	7	14	HS1
H3X	8	13	WDIB
H3Y	9	12	WDI
V _{CC}	10	11	$\overline{\text{WSER}}$


(Top view)

HA166152FP4

Pin Description

Pin No.	Symbol	Pin Name	Description
1	GND	Ground	Ground pins
2, 3	H0X, H0Y	Head 0X, 0Y	These pins are connected to the $\overline{R/W}$ head coil of channel 0.
4, 5	H1X, H1Y	Head 1X, 1Y	These pins are connected to the $\overline{R/W}$ head coil of channel 1.
6, 7	H2X, H2Y	Head 2X, 2Y	These pins are connected to the $\overline{R/W}$ head coil of channel 2.
8, 9	H3X, H3Y	Head 3X, 3Y	These pins are connected to the $\overline{R/W}$ head coil of channel 3.
10	V _{CC}	5 V	5 V power supply
11	$\overline{WSER}$	Servo write switch	When $\overline{R/W}$ and $\overline{WSER}$ are set low, all write drivers are selected. Refer to the Mode Select Table.
12, 13	WDI, WDIB	Write data input	Write data input pin. The signal is divided in the IC, and drives the write driver.
14 15	HS1 HS0	Head select 1 Head select 0	Input pins for head select signals. The combination of these signals selects one head from head 0 to head 3. Refer to the head select table.
16, 17	RDX, RDY	Read amplifier output	Differential output pins for the read amp. The signal read out from the head coil is amplified and provided on these pins.
18	WC	Write current setting	Write current setting pin. The write current is defined by the equation below by connecting the external resistance R_{WC} between this pin and GND. $\text{Write current [mA]} = K/R_{WC} \text{ [k}\Omega\text{]}$
19	$\overline{R/W}$	$\overline{R/W}$ switch	Mode select switch for changing over the bias condition of the head coil A low level selects the write mode, while a high level selects the read mode.
20	$\overline{CS}$	Chip select	When this line is set high, the circuit goes into the idle state, a low power state. When this line is low, the chip is active.

Block Diagram



Absolute Maximum Ratings (T_a = 25°C)

Item	Symbol	Rating	Unit	Applicable Terminal
Supply voltage	V _{CC}	-0.3 to +6.0	V	V _{CC}
Write current	I _W	35	mA	
Interface input voltage	V _{IN}	-0.3 to V _{CC} +0.3	V	HS0, HS1, WDI, WDIB, WSER, R/W, CS
Read data output current	I _{RO}	-10	mA	RDX, RDY
Operating temperature	T _{opr}	0 to +70	°C	
Storage temperature	T _{stg}	-55 to +150	°C	
Head voltage swing	V _{HSW}	4.0	V _{pp}	
Power dissipation	P _T	550	mW	

HA166152FP4

Power Supply (Ta = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Conditions
Supply voltage range	V _{CC}	4.5	—	5.5	V	
+5.5 V supply current	I _{CC}	—	39	52	mA	Read mode
		—	35 + I _W	43 + I _W		Write mode
		—	7	11		Idle mode

Electrical Characteristics (V_{CC} = 5 V, Ta = 25°C unless otherwise specified)

Digital Input

Item	Symbol	Min	Typ	Max	Unit	Test Conditions
Low level input voltage1	V _{IL1}	−0.3	—	0.8	V	
Low level input current1	I _{IL1}	−100	—	—	μA	V _{IL} = 0.4 V
High level input voltage1	V _{IH1}	2.0	—	V _{CC} + 0.3	V	
High level input current1	I _{IH1}	—	—	20	μA	V _{IH} = 2.0 V
Low level input voltage2	V _{IL2}	V _{CC} − 2	—	V _{CC} − 1.65	V	(WDI, WDIB)
Low level input current2	I _{IL2}	—	—	0.75	mA	V _{IL} = 3.2 V (WDI, WDIB)
High level input voltage2	V _{IH2}	V _{CC} − 1	—	V _{CC} + 0.3	V	(WDI, WDIB)
High level input current2	I _{IH2}	—	—	0.95	mA	V _{IH} = 4.2 V (WDI, WDIB)
Read/write transition time	t _{RW}	—	—	150	ns	
Write/read transition time	t _{WR}	—	—	500	ns	
Head select switching delay time	t _{HS}	—	—	1000	ns	Read mode
Chip disable transition time	t _{IRW}	—	—	1000	ns	Idle to read

Head Select Table

HS1	HS0	Head Selected
L	L	0
	H	1
H	L	2
	H	3

Mode Select Table

R/W	WSER	Mode
L	L	Servo Write*1
	H	Write
H	L	Prohibition
	H	Read

Note: 1. When R/W and WSER are set from high to low, R/W and WSER must be switched at same timing and HS0, HS1 must be set high level.

Read Amplifier

Item	Symbol	Min	Typ	Max	Unit	Test Conditions
Differential voltage gain	Avd	300	345	390	V/V	f = 300 kHz
Bandwidth	B _w	(90)*1	(150)*1	—	MHz	−3 dB
Input noise voltage	V _n	—	(0.5)*1	(0.6)*1	nV/√Hz	f ≤ 15 MHz, Inputs shorted
Common mode rejection ratio	CMRR	60	80	—	dB	
Power supply stability	PSRR	45	60	—		V _{CC} ±100 mVp-p, f = 5 MHz
Channel separation	Sep	60	80	—		V _{in} = 100 mVp-p on unselected channels and V _{in} = 0 mVp-p on selected channels, f = 5 MHz
Output offset voltage	V _o	−300	—	300	mV	Inputs shorted
Differential input impedance	R _{in}	—	0.72	—	kΩ	f = 300 kHz
			0.70			f = 5 MHz
Common mode output voltage	V _{com}	2.0	2.5	3.0	V	
Output source current	I _{OSO}	—	−10	—	mA	
Output sink current	I _{OSI}	1.5	2.0	—		
Input capacitance	C _{IN}	—	(10)*1	(15)*1	pF	

Note: 1. These values are only for design purpose.

HA166152FP4

Write Driver

Item	Symbol	Min	Typ	Max	Unit	Test Conditions
Write current setting range	I_W	5	—	30	mA	
Head current rise time	t_{hex}	—	4	15	ns	$L_h = 0 \mu H$, $R_h = 0 \Omega$, 10% to 90% point
Head current switching delay time	t_{d3}	—	—	30		$R_h = 0 \Omega$, $L_h = 0 \mu H$, from 50% point
Head current switching symmetry	t_{d4}	—	—	(1)*1		WDL duty cycle = 50%, rise/fall time = 1 ns
Head current gain	I_H/I_{WC}	—	19	—	A/A	Head current/ I_{WC}
WC output voltage	V_{WC}	—	2.8	—	V	
Write current accuracy1	I_{H1}	9.45	10.5	11.55	mA	$R_{WC} = 5 k\Omega$
Write current accuracy2	I_{H2}	18.0	20.0	22.0	mA	$R_{WC} = 2.5 k\Omega$
Write current accuracy3	I_{H3}	27.0	30.0	33.0	mA	$R_{WC} = 1.6 k\Omega$

- Note: 1. These values are only for design purpose.
 2. Write current constant : K is determined by the following equation.

$$K = 54.8 - 0.23 I_W \text{ (mA)}$$






Figure.1 The relation between K and I_W

Timing Waveforms



HA166152FP4

Application Circuit Example



Unit R:
C: F

Notes: 1. External resistance value R_{WC} is determined by following equation.


$$R_{WC} [k\Omega] = \frac{K}{\text{Write current [mA]}}$$

Also, write current ringing on changeover between read and write can be suppressed by locating the resistor R_{WC} as close as possible to the WC pin.

2. When the length of the wiring pattern increases, the RDX and RDY outputs might have some oscillation. This oscillation can be eliminated by inserting series resistors on these outputs as close to the pins as possible.

Package Dimensions

Unit: mm



When using this document, keep the following in mind:

1. This document may, wholly or partially, be subject to change without notice.
2. All rights are reserved: No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without Hitachi's permission.
3. Hitachi will not be held responsible for any damage to the user that may result from accidents or any other reasons during operation of the user's unit according to this document.
4. Circuitry and other examples described herein are meant merely to indicate the characteristics and performance of Hitachi's semiconductor products. Hitachi assumes no responsibility for any intellectual property claims or other problems that may result from applications based on the examples described herein.
5. No license is granted by implication or otherwise under any patents or other rights of any third party or Hitachi, Ltd.
6. MEDICAL APPLICATIONS: Hitachi's products are not authorized for use in MEDICAL APPLICATIONS without the written consent of the appropriate officer of Hitachi's sales company. Such use includes, but is not limited to, use in life support systems. Buyers of Hitachi's products are requested to notify the relevant Hitachi sales offices when planning to use the products in MEDICAL APPLICATIONS.

HITACHI

Hitachi, Ltd.

Semiconductor & IC Div.
Karukozaka MN Bldg., 2-1, Ageba-cho, Shinjuku-ku, Tokyo 162, Japan
Tel: Tokyo (03) 3266-9376
Fax: (03) 3235-2548

For further information write to:

Hitachi America, Ltd.
Semiconductor & IC Div.
2000 Sierra Point Parkway
Brisbane, CA. 94005-1835
U S A
Tel: 415-589-8300
Fax: 415-583-4207

Hitachi Europe GmbH
Electronic Components Div.
Continental Europe
Hans-Pinsel-Strasse 10a
D-8013 Haar bei München
F. R. Germany
Tel: 089-46140
Fax: 089-463068

Hitachi Europe Ltd.
Electronic Components Div.
Northern Europe Headquarters
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA
United Kingdom
Tel: 0628-585000
Fax: 0628-778322

Hitachi Asia (Hong Kong) Ltd.
Unit 706, North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon
Hong Kong
Tel: 7359218
Fax: 7306071

Hitachi Asia Pte. Ltd.
78 Shenton Way #11-01
Singapore 0207
Tel: 221-6131, 7355
Fax: 225-4225, 221-4474