

# USB 3.1 Gen 2 Type C Connector

Superior performance up to 10Gb/s

## COMPACT, HIGHLY RELIABLE, HIGH SPEED CONNECTOR

USB 3.1 Type C Gen 2 is the future of the USB technology providing multifunction single cable solution for Data, Power, Audio and Video. The slim form factor supports the evolving design trends. The reversible design enables quick and easy connections no matter which way it is inserted. It supports scalable power delivery up to 100W and performance speed up to 10Gb/s.

- Supports SuperSpeed communication 10Gb/s
- Reversible plug and cable orientation
- Slim and sleek design
- Better EMI shielding design



### TARGET MARKETS



### FEATURES

- Supports SuperSpeed communication 10Gb/s
- Reversible plug and cable orientation
- Robust and small form factor design
- Better EMI (Electromagnetic Interference) shielding design
- RoHS compliant and lead-free

### BENEFITS

- Minimizes user waiting time
- Ready for next-generation applications
- Ensures quick and easy connections whichever way it is inserted
- Tailored for emerging product designs
- Suitable for applications in very thin platforms and the I&I market
- Protects against EMI and ESD (Electromagnetic Discharge)
- Meets environmental, health and safety requirements

## ▶ USB 3.1 Gen 2 Type C Connector

### TECHNICAL INFORMATION

#### MATERIAL

- Housing: High Temperature Thermoplastic
- Shell: Stainless Steel
- Terminal: Copper Alloy

#### MECHANICAL PERFORMANCE

- Mating Force: 5 to 20N
- Durability: 10,000 mating cycles

#### ELECTRICAL PERFORMANCE

- Low Level Contact Resistance:
  - Initial: 40mΩ max.
  - $\Delta R = \pm 10m\Omega$  max. after environmental stress
- Insulation Resistance: 100MΩ min.
- Transfer SuperSpeed: 10Gb/s
- Voltage Rating: 100VAC/DC
- Current Rating:
  - 5.0A for VBUS and GND
  - 1.25A for Vconn and GND
  - 0.25A for all other contacts

#### PACKAGING

- Receptacle: Tape/Reel
- Plug: Tray

### PART NUMBERS

Description	Orientation	Mounting Style	Part Numbers
USB 3.1 Type C Gen 2 receptacle	Right angle	Top mount SMT + DIP (Long shell)	10133476-10001LF
USB 3.1 Type C Gen 2 receptacle	Vertical	Top mount dual SMT	10132328-10011LF
USB 3.1 Type C Gen 2 plug	-	-	10133475-10001LF
USB 3.1 Type C Gen 2 receptacle	Right angle	Top mount dual SMT (Short body)	10137737-10001L

#### SPECIFICATION

- Amphenol Product Specification: GS-12-1351

#### ENVIRONMENTAL

- Operating Temperature: -55°C to 85°C

#### TARGET MARKETS/APPLICATIONS



Infotainment



Adaptor  
Flash Drive  
Laptop  
Phone  
Portable Power Bank  
Portable HDD  
Tablet  
Wearable Device



Motherboard Add-on Card  
Storage Adaptor  
Storage Enclosure



Factory Automation Equipment  
Industrial Equipment