


## SRMB2.5/15-FW1-15B

- 30 Connections
- Direct mounting
- With labelling on both sides





Phoenix Mecano Brand

## Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm <sup>2</sup>	Material	PA 6.6
Solid max	4.0 mm <sup>2</sup>	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm <sup>2</sup>	Temperatures	
Stranded (flexible) max	4.0 mm <sup>2</sup>	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm <sup>2</sup>	Dimensions	
Stranded with Ferrule max	2.5 mm <sup>2</sup>	Stripped Length	7.0 mm
Clamping Range min	0.2mm <sup>2</sup>	Width	5.0 mm
Clamping Range max	4.0 mm <sup>2</sup>	Height	23.0 mm
		Length	90.9 mm
		Length Hole Direct Mounting	83.8 mm

## Colours

-  BEIGE, similar RAL 1019
-  BLUE, similar RAL 5015

## Connection Diagram



## Order Data

Article Designation	Article Number	PU
SRMB2.5/15-FW1-15B-BEIGE	41361.2	20
SRMB2.5/15-FW1-15B-BLUE	41361.5	20

## Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQI2/5/11	492032.0	50
External Cross-Connector insulated AQI3/5/11	492033.0	50
External Cross-Connector insulated AQI4/5/11	492044.0	10
External Cross-Connector insulated AQI10/5/11	492045.0	10

## Ratings

Ratings	UR		IEC
	Rated Voltage	300 V	300 V
Rated Current	20 A	20 A	24 A
Rated Wire Size	AWG 22-12	AWG 22-12	2.5 mm <sup>2</sup>
Rated Impulse Voltage			6 V
Pollution Degree			3