



Spade and Ring Series Pre-Insulated

.240 Spade
.031 Electro-Tinned Copper
16-14 AWG (Blue)

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER
		.147	.200	.250					
	0	X			B	✓	✓	4000	50005
			X		B	✓	✓	3000	50005-8
				X	B	✓	*	3000	50005-8A
		X			W	✓	✓	4000	50006
			X		W	✓	✓	3000	50006-8
				X	W	✓	*	3000	50006-8A
	2	X			B	✓	✓	4000	50013
			X		B	✓	✓	3000	50013-8
				X	B	✓	*	3000	50013-8A
		X			W	✓	✓	4000	50014
			X		W	✓	✓	3000	50014-8
				X	W	✓	*	3000	50014-8A
	4	X			B	✓	✓	4000	50021
			X		B	✓	✓	3000	50021-8
				X	B	✓	*	3000	50021-8A
		X			W	✓	✓	4000	50022
			X		W	✓	✓	3000	50022-8
				X	W	✓	*	3000	50022-8A
	6	X			B	✓	✓	4000	50029
			X		B	✓	✓	3000	50029-8
				X	B	✓	*	3000	50029-8A
		X			W	✓	✓	4000	50030
			X		W	✓	✓	3000	50030-8
				X	W	✓	*	3000	50030-8A

Spade and Ring Series Pre-Insulated

.300 Spade
.020 Pre-Tinned Brass
16-14 AWG (Blue)

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER
		.147	.200	.250					
	4	X			B	✓	✓	4000	50169-200
			X		B	✓	✓	3000	50169-200-8
				X	B	✓	*	3000	50169-200-8A
	6	X			B	✓	✓	4000	50181-200
			X		B	✓	✓	3000	50181-200-8
				X	B	✓	*	3000	50181-200-8A
	8	X			B	✓	✓	4000	50193-200
			X		B	✓	✓	3000	50193-200-8
				X	B	✓	*	3000	50193-200-8A
	10	X			B	✓	✓	4000	50205-200
			X		B	✓	✓	3000	50205-200-8
				X	B	✓	*	3000	50205-200-8A

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$

* Contact Factory for Latest Agency Approvals.