

E-Series Plug-In Mixer

0.025 - 200 MHz

EMS-3

V3.00

Features

- LO Power: +7 dBm
- Up to +1 dBm RF

Specifications @ 25°C

Frequency Range		
RF		0.025 - 200 MHz
LO		0.025 - 200 MHz
IF		DC - 200 MHz
Conversion Loss (dB)		Maximum
0.05 - 100 MHz	Typical 5.5	7.5
.025 - 200 MHz	6.0	8.5
Isolation (dB)		Minimum
LO to RF	Typical	
0.025 - 0.25 MHz	55	50
0.25 - 100 MHz	45	30
100 - 200 MHz	35	25
LO to IF		
0.025 - 0.25 MHz	45	35
0.25 - 100 MHz	40	30
100 - 200 MHz	30	20

Operating Characteristics

Impedance	50 Ohms Nominal
RF input for 1dB Compression	+ 1 dBm


Ordering Information

Part No.	Packaging
EMS-3	Tube
EMS-3TR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	50 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to 100°C
Operating Temperature	-55°C to 100°C
Pin Temperature (10 Seconds)	260°C

R-1



Dimensions in () are in mm.
 Unless Otherwise Noted: .x = ±0.04 (1.00)
 .xx = ±0.02 (0.50)
 .xxx = ±0.010 (0.250)
 WEIGHT (APPROX.): 0.16 OUNCES 4.4 GRAMS

Pin Configuration

Function	Pin No.
LO	8
RF	1
IF*	3,4
Ground	2,5,6,7

* IF pins must be connected together externally.

S 0099 B

Specifications Subject to Change Without Notice.

M/A-COM, Inc.

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595
 Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020