




Telecommunication ISDN U Transformer Transformers

DT22-1503



DIMENSIONS IN mm

A	B	C	D	E	F	G
25.0 MAX.	26.0 MAX.	22.0 MAX.	17.5 MAX.	3.3±0.5		

ELECTRICAL CHARACTERISTICS	
URNS RATIO	N2:N1 0.8±2% @10KHz, 1V N3:N1 0.8±2% @10KHz, 1V
INDUCTANCE	SEC: 14.5 mH ± 10% @10KHz, 1V I _{dc} =60mA
LEAKAGE INDUCTANCE	90 uH Max. @10KHz, 1V
D.C. RESISTANCE	PRI: 2.8 Ω Max. SEC: 2.7 Ω Max.
INTERWINDING CAPACITANCE	100 pF Max. @10KHz, 1V
DIELECTRIC STRENGTH	2000 VAC, 2 SEC @PRI TO SEC 2000 VAC, 2 SEC @WDG TO CORE

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

<http://www.deltaww.com>